Date of publication xxxx 00, 0000, date of current version xxxx 00, 0000. Digital Object Identifier 10.1109/ACCESS.2017.DOI

# Determining Distributions of Security Means for WSNs based on the Model of a Neighbourhood Watch

BENJAMIN FÖRSTER<sup>1</sup>, PETER LANGENDÖRFER<sup>2</sup>, AND THOMAS HINZE.<sup>3</sup>

<sup>1</sup>Wireless Systems, Innovations for High Performance Microelectronics, Im Technologiepark 25, Frankfurt (Oder), Germany (e-mail: bfoerster@ihp-microelectronics.com)

<sup>2</sup>Wireless Systems, Innovations for High Performance Microelectronics, Im Technologiepark 25, Frankfurt (Oder), Germany (e-mail: langendoerfer@ihp-microelectronics.com)

<sup>3</sup>Faculty of Biological Sciences, Friedrich Schiller University Jena, Ernst-Abbe-Platz 2, Jena, Germany (e-mail: thomas.hinze@uni-jena.de)

Corresponding author: Benjamin Förster (e-mail: bfoerster@ihp-microelectronics.com).

**ABSTRACT** Neighbourhood watch is a concept allowing a community to distribute a complex security task in between all members. Members carry out security tasks in a distributed and cooperative manner ensuring their mutual security and reducing the individual workload while increasing the overall security of the community. Wireless sensor networks (WSNs) are composed of resource-constraint independent battery driven computers as nodes communicating wirelessly. Security in WSNs is essential to prevent attackers from eavesdropping, tampering monitoring results or denying critical nodes from providing their services and potentially cutting off larger network parts. WSN security is crucial to prevent attackers from eavesdropping, tampering monitoring results or denying critical nodes to cut off larger network parts. The resource-constraint nature of sensor nodes prevents them from running full-fledged security protocols. Instead, it is necessary to assess the most significant security threats and implement specialised security solutions. A neighbourhood watch inspired distributed security scheme for WSNs has been introduced by Langendörfer aiming to increase the variety of attacks a WSN can fend off. The framework intends to statically distribute requirement-based selections of online security means intended to cooperate in close proximity on large-scale static homogeneous WSNs. A framework of such complexity has to be designed in multiple steps. We determine suitable distributions of security means based on graph partitioning concepts. The partitioning algorithms we provide are NP-hard. To evaluate their computability, we implement them as 0-1 linear programs (LPs) and test them on WSN models generated with our novel  $\lambda$ -precision unit disk graph (UDG) generator.

**INDEX TERMS** Cooperative Security Framework, Distributed Security Means, Graph Generator, Linear Programming, Neighbourhood Watch, Unit Disk Graphs, Wireless Sensor Networks

### I. INTRODUCTION

WSNs are networks consisting of independent low power computing units called nodes that run on battery, communicate wirelessly and carry out a monitoring or controlling tasks. Information gathered by sensor nodes are transmitted to base stations. In large-scale static homogeneous WSNs considered in this work, the communication is often done hop-by-hop. Additionally, only a small subset of nodes is connected to a base station (BS). The term static means that the nodes in the network are immobile and placed at a fixed position. Homogeneous implies that all nodes in the network have the same hardware capabilities. In large-scale WSNs, information to and from nodes are transmitted via intermediate nodes (hop-by-hop). Especially when applied to critical infrastructures, WSNs need to ensure certain security attributes regarding transmitted data. In general, WSNs are vulnerable to a multitude of attacks. Therefore, security risks have to well assessed and covered in the design of the network. The limited computational power and energy supply of nodes constrain the types and complexity of security means applied to WSNs. Hence, we have to compromise between security and lifetime of a WSN. To compromise with regards to the longevity of the network, it is necessary to identify the most likely and costly threats and select security means accordingly. Attack defence trees are well-established method for a risk assessment in WSNs [1]. In [2], Langendörfer proposed an extended concept of attack defence trees considering the resource limitations of the underlying nodes called "Attack Defence Resource Trees" (ADRT). This allows a selection of security means specifically tailored to the area of application of a WSN and the resulting most likely threat scenarios. Even with an optimal selection of security means, the coverage of a larger scope of threat scenarios is limited.

Therefore, a neighbourhood watch inspired online security framework with a static distribution of cooperating security means has been presented in [2]. For an optimal selection of security means resulting in an increased threat coverage, it is necessary to adapted risk assessment. Hence, the ADRTs are further extended by the cooperative component to "Cooperation-based Attack Defence Resource Trees" in [2]. The complex task of automated selection of security means and their resulting effect on the qualitative and quantitative security attributes of a WSN is challenging. In [3] the authors attempt a tool-supported security focussed component-based design of WSNs by selecting optimal subsets of security means. Further, a lot of research has been conducted to evaluate qualitatively and quantitatively the security of networks [4]. Only a small portion of research directly addresses WSNs [5], [6]. A security metric to evaluate cooperative intrusion detection systems (IDSs) [6] potentially creates a reliable basis for a future evaluation and automated design of neighbourhood watch inspired security framework. We expect such a framework to provide a better compromise between the two major goals of WSNs security. Increasing either or both of the following: the network lifetime with regards to the energy supply and the threat coverage. In a WSN as well as a community, a number of individuals share a common environment. Therefore, it can be observed that individual parties of the same community band together to distribute the security task among them and ensure their mutual security reducing their individual workload. This concept is known as neighbourhood watch. To design a static online security framework and implementing a cooperative security strategy requires several steps. A proper distribution of security means has to be determined. A set of suitable security means has to be evaluated and adapted. A cooperative distributed online security scheme creates a significant communication overhead.

Finally, a concept created from a multitude of components needs a certain degree of hardware independence to ensure its reusability for different sensor nodes with minimal manual adaptation. Therefore, a virtualisation concept or abstraction layer has to be considered [7]. Since we consider large-scale static WSNs, the cooperative security framework needs to execute security at least partially online (on and between the nodes) to enable timely threat reactions. A fundamental assumption towards a framework utilising a static distribution of security means to be successful is that the attacker has no knowledge at the insider level. Therefore, an attacker holds no knowledge about the distribution of security means.

In this paper, we propose distributions of security means in large-scale static homogeneous WSNs that favour a neigh-

bourhood watch inspired security framework. To mark out the borders of our model, we make a number of considerations. There are three scenarios of cooperating security means we are going to evaluate: a single security mean per node, a fixed number of security means can be applied per node, a loadbased distribution of variable number of security means per node. For the latter one, it is necessary to pinpoint a common resource capacity per node for all nodes available for security tasks and a resource requirements for all considered security means. To determine the distributions, we model the WSNs as undirected graphs in which the nodes represent sensor nodes. Edges of the graph express the reachability of nodes in transmission range within the underlying WSN. In order to distribute the security means, we determine 0-1 linear programs (LP) to compute suitable optimal graph partitions. Optimal with regards to our model and the defined objective function The 0-1 LPs fall into the complexity class of non-deterministic polynomial time (NP) hard problems [8]. Therefore, it is necessary to empirically evaluate whether an optimal solution is within the timely computable bounds of our input sizes for large numbers of networks with realistic topologies and node numbers. Network sizes of WSNs with 20 up to 300 nodes have been evaluated. The graphs representing the WSNs for the evaluation process have been generated as random  $\lambda$ -precision unit disk graphs (UDGs). A UDG is an undirected geometric graph in which each node has a fixed position in euclidean space and two nodes have a common edge if their distance is below a fixed threshold (transmission range) common for all nodes. A  $\lambda$ -precision graph is a geometric graph in which all pairs of nodes are at least  $\lambda$  apart. To generate desired graph topologies, we provide a table of generator seeds for combinations of node numbers, desired average node degrees and covered generation plane space. Seeds are the input values for the generator that are likely to result in random graphs with desired properties. The average node degree is the arithmetic mean of edges connected to each node for all nodes in a graph. The generation plane is in our context a unit square in which the nodes of our random graphs are distributed. The generator is written in Python and utilises the NetworkX library [9] to some degree. It allows to create graphs with an even degree distribution and a low variance of the local cluster coefficient controllable via  $\lambda$ . The local cluster coefficient is a measure indicating the connectivity of the neighbourhood of a node. The generator allows further manipulations of graph properties like enabling to enforce a desired average node degree and receiving connected bridgefree graphs. The 0-1 LPs have been evaluated using Python with Pyomo [10] and Gurobi [11] to model and solve the linear optimisation problems partitioning the graphs for an optimal distribution of security means.

In Section II, we familiarise the reader with mathematical terms and definitions necessary for the understanding of the paper. Section III discusses the state of the art regarding distributed security solutions, dominating sets and domatic partitions as well as graph generators for large-scale static homogeneous WSNs. Subsequently in Sections IV and V, we illustrate the graph partitioning concept for the neighbourhood watch inspired security scheme introduced in [2]. Followed by Section VI, we introduce a  $\lambda$ -precision UDG generator for large-scale static homogeneous WSNs. In Section VII, we accustom the reader with the test setup to evaluate the computability of the introduced graph partitioning concepts that have been modelled with 0 – 1 linear programs (LPs) and computed on the  $\lambda$ -precision UDGs created by our introduced graph generator. Finally, we present and analyse the test results in Section VIII and conclude different achievements of our paper in Section IX.

### **II. BACKGROUND**

We introduce mathematical terms and definitions related to graph theory and mathematical optimisation as well as terms necessary for the empirical evaluation.

**Cardinality of Sets:** The cardinality of a set indicates the number of elements a set contains notated as follows  $|\{\cdot\}|$ .

**Undirected Graph:** An undirected irreflexive graph G = (V, E) is defined as a finite set of nodes V and a set of edges:

$$E \subseteq \{\{v, w\} | v, w \in V \land v \neq w\}$$

$$(1)$$

Throughout this work, we exclusively utilise undirected and irreflexive graphs.

**Subgraph:** A subgraph of an undirected graph G = (V, E) is defined as SG = (V', E') with  $V' \subseteq V$  and  $E' \subseteq E$  with  $\forall \{v, w\} \in E' : v, w \in V'$ .

**Connected Graph:** An undirected graph is connected when there are no two nodes in the graph without a path.

**Connected Component:** In an undirected graph, a connected component is a connected subgraph that is not part of any larger connected subgraph.

**Bridge:** In an undirected graph consisting of  $c \in \mathbb{N}_{>0}$  connected components, a bridge is an edge, whose absence decomposes it into c + 1 connected components.

**Bridge Path:** In an undirected graph G = (V, E), there is a bridge path between nodes *u* and *v* iff there is a unique cycle-free path *P* exclusively composed by a sequence of bridges over a subset of nodes from  $V \setminus \{u, v\}$  connecting *u* with *v* in which all contained nodes except *u* and *v* have a node degree of two and it does not exist any longer path *Q* with the same properties containing *P*.

**Geometric Graph:** A geometric graph is an undirected graph in a *d*-dimensional metric space  $[0, 1)^d$  and edges are added based on their pairwise distance  $r_{tr}$  (transmission range) determined by a defined distance function. The distance  $r_{tr}$  in a geometric graph is fix for all nodes and node pairs of the graph. Throughout this work, we always refer to this distance

as  $r_{\rm tr}$ .

**Random Geometric Graph:** A random geometric graph (RGG) is a geometric graph in which nodes are placed randomly.

**Unit Disk Graph:** A unit disk graph (UDG) is a geometric graph in a two-dimensional euclidean space with an euclidean distance metric applied to them.

 $\lambda$ -precision Graph: A  $\lambda$ -precision graph is a geometric graph in which the minimal distance between each pair of nodes is at least  $\lambda$ .

**Neighbourship Function:** We define the neighbourship of a node *v* in an undirected graph G = (V, E) with  $v, w \in V$  as follows:

$$N[v] := \{w | \{v, w\} \in E\} \cup \{v\}$$
(2)

**Node Degree:** A node degree of a node  $v \in V$  of an undirected graph G = (V, E) is the number of edges of the graph the node participates in:

$$\deg[v] = |\{e | \forall e \in E : v \in e\}|$$
(3)

Average Node Degree: The average node degree of an undirected graph G = (V, E) is the arithmetic mean of the node degree of each node in the graph relative to the number of nodes as follows:

$$\deg_{\text{avg}}[G] = \sum_{\nu \in V} \frac{\deg[\nu]}{|V|} \tag{4}$$

**Local Cluster Coefficient:** The local cluster coefficient is a measure indicating how well the neighbourhood of a node is connected. Following [12], the local clustering coefficient for undirected graphs is defined as:

$$C[v] = \frac{2 \cdot |\{e|e \in E \land e = \{w, u\} \land w, u \in N[v] \setminus \{v\}\}|}{|N[v] \setminus \{v\}| \cdot (|N[v] \setminus \{v\}| - 1)}$$
(5)

**Variance of the Node Degree Distribution:** We define the variance of the node degree distribution for a RGG G = (V, E) as follows:

$$\operatorname{Var}_{\operatorname{deg}}[G] = \sum_{v \in V} \frac{\left(\operatorname{deg}[v] - \operatorname{deg}_{\operatorname{avg}}[G]\right)^2}{|V|} \tag{6}$$

**Linear Program:** A LP or linear optimisation is a method which tries to optimise a mathematical model based on linear relationships with the following standard form:

$$\begin{array}{ll} \max \quad \mathbf{c}^{T} \cdot \mathbf{x} & & \ \end{array} \begin{array}{l} \text{objective function} \\ \text{s.t.} \quad \begin{array}{l} \mathbf{A} \cdot \mathbf{x} & \leq \mathbf{b} \\ \mathbf{x} & \geq \mathbf{0} \end{array} \end{array} \right\} \text{constraints}$$
(7)





FIGURE 1: The set of green nodes is a dominating set in the given graph.



FIGURE 2: The example shows a graph in which the nodes are mapped to a domatic partition consisting of three dominating sets.

with the vectors  $\mathbf{b}$  and  $\mathbf{c}$  and with a matrix  $\mathbf{A}$  that have to be known to the problem. The vector  $\mathbf{x}$  contains the variables whose values have been optimised. Linear programs are called in this way because the objective function as well as the equality and inequality constraints are linear.

In a 0-1 linear program, the components of the vector of variables  $\mathbf{x}$  is bound to  $\{0, 1\}$ . For integer linear programming as well as 0-1 linear programming without objective function it is known that they belong to the class of NP complete problems [8]. With objective function, their complexity is not bound to an upper limit and the problems are therefore considered to be NP hard. However, experience has shown that 0-1 linear programs perform better than integer linear problems even when they rely on significantly more variables.

**Dominating Set:** A dominating set *D* is a set of nodes of an undirected graph G = (V, E) for which holds:

$$D \subseteq V \text{ whereas } \forall v \in V : D \cap N[v] \neq \emptyset$$
(8)

In Fig. 1, an example for a dominating set of nodes for a graph is given. As the definition implies, every node in this graph is either part of the dominating set or adjacent to a node from the set.

**Domatic Partition:** A domatic partition  $\mathbb{D}(G)$  is a decomposition of nodes *V* of a graph G = (V, E) into disjoint dominating sets with:

$$\bigcup_{D\in\mathbb{D}} D = V \land \bigcup_{\substack{D_1, D_2\in\mathbb{D}\\D_1\neq D_2}} D_1 \cap D_2 = \emptyset$$
(9)

A domatic partition can also be defined using the neighbourship term of graphs. Then, a set of dominating sets in G

$$\mathbb{D}(G) = \{ D | D \subseteq V, \, \forall v \in V : \, D \cap N[v] \neq \emptyset \}$$
(10)



FIGURE 3: The partition of the graph is not a domatic partition because there exist nodes in at least one dominating set of the partition that has no neighbourship with at least one node of each of the other dominating sets of the partition.

is a domatic partition iff Equation (9) holds. We define a *n*-domatic partition as a partition of G into *n* disjoint dominating sets. An example can be seen in Fig. 2. When referring to a node satisfying the properties of a domatic partition, the set consisting of the node itself and its adjacent nodes have to have a non-empty intersection with all sets of the domatic partition:

$$v \in V : \forall D \in \mathbb{D} : N[v] \cap D \neq \emptyset \tag{11}$$

In Fig. 3, we provide an example for a partition in which a number of nodes does not satisfy the definition of a domatic partition. A domatic partition of a WSN ensures that each sensor node has at least one direct neighbour of each dominating set of the partition or is a member of the set. The size of the domatic partition is given by the number of different security means that have been applied to the network. All sensor nodes in the same dominating set of the partition implement the same security mean. In case all nodes in the same dominating set implement the same security mean, we achieve a distribution of security means in which all nodes either implement a security mean or are directly adjacent to a node that does. Therefore, the set of sensor nodes and its neighbours have no empty intersection with any of the sets of the partition. Hence, all security means applied to the WSN are present in the neighbourship of each node.

### **III. RELATED WORKS**

In [2] a neighbourhood watch inspired concept for a cooperative distributed static security framework has been introduced. The objective of distributed security solutions is to cover a wider range of threat scenarios in a large-scale static homogeneous WSN. This section is divided into three parts. The first subsection explores research work towards distributed security solutions for WSNs. The second part evaluates existing research regarding dominating sets and domatic partitions. In the third subsection, we discuss graph generators as model for WSNs.

### A. DISTRIBUTED SECURITY SOLUTIONS FOR WSNS

A number of publications propose cooperating security means for WSNs that provide mutual protection. The paper [13] introduces a security framework concept for static heterogeneous WSNs. Each set of nodes is assigned to a cluster head (CH) (a more powerful sensor node). Nodes running IDSs

notify their associated CH about identified threats or CH are informed by CHs in close proximity. If a threat is detected and communicated to a CH it will be propagated to other CHs in the WSN. Clusters that consider the threat imminent for their own cluster react by redistributing security means on associated nodes based on the threat scenario. Therefore, the CH holds a set of security means which can be implemented on or revoked from the sensor nodes. This allows a dynamic threat evaluation and flexible reactions. The proposed security framework for static heterogeneous WSNs [13] has been tested in a simulation including a network with 2000 regular nodes and 10 gateway nodes. The energy consumption was only evaluated for regular nodes, for CHs it was considered unlimited. To test the simulated sensor network, seven abstract attack patterns have been implemented and for each scenario 200 sequential attacks have been executed. The authors of [13] evaluated the simulation based on two metrics, the success rate (number of nodes alive after an attack) and the energy consumption (average percentage of energy of all surviving nodes). For comparison, WSNs implementing one security mean or multiple static security scheme frameworks have been used. The results show that the proposed framework provides the highest success rate while also consuming the highest amount of energy in each simulation. The contribution [14] presents a security framework that has been developed and implemented on a real WSN based on [13]. The test of the resulting security framework has been executed on a rather small WSN with only six nodes. One node acted as the CH which communicated directly to a base station. The authors assumed two kinds of attack scenarios. One in which only a single kind of attack is started on the WSN and one in which two kinds of attack are launched in succession. The results show that the WSN implementing the framework was able to recover from all tested attacks even when they have been executed successively. The energy consumption has not been considered. Both papers propose a security solution with distributed security means for heterogeneous WSNs with rather powerful CHs. The heterogeneity of the WSN is not utilised by the frameworks to which the proposed one is compared. The according statement from [14] has very limited meaningfulness due to their limitation in executed test scenarios, measured parameters and small network size.

IDSs are distinguishable by many criteria [15]. Whether the intrusion detection is executed online, offline or hybrid states if certain tasks are performed on nodes or on a centralised base station affecting whether a timely reaction is possible. Based on their detection strategy, IDSs can be classified as anomaly-based, signature-based or hybrid. [16] introduces a distributed neighbour based IDS. Each node monitors a set of neighbouring nodes by storing their attribute vectors sending warnings to other nodes in case a malicious anomaly has been recognised. If a number of nodes communicate the same anomaly, the network acts accordingly. There are distinctions based on the intrusion and intruder type and so on. A comprehensive overview of the classification IDSs is provided in [15]. The publication [16] is built upon [17] which

VOLUME 4, 2016

describes a similar distributed approach to detect misbehaving sensor nodes in local areas by comparing their behaviour vector with vectors from other direct neighbours. Another popular concept is LiDeA citekrontiris2008lidea. Nodes that detect irregularities in the network notify other close-by nodes to establish a vote. Notified nodes decide about the handling of the irregularity as well as the suspicious node. Therefore, nodes provide a number of modules that can be activated on demand and based on received information by broadcasting neighbours. Whether a node is assumed to be an intruder is determined based on a majority vote. In [18] a lightweight, energy-efficient IDS using mobile agents is introduced. These agents are sent through the network as regular messages and are temporally installed on addressed nodes. Therefore, IDSs are dynamically distributed and instead of running on nodes permanently. While agents are run by nodes, they collect information about their energy consumption and initiate warnings to the network if noticeable deviations are recognised. The transmission and installation of changing IDSs on nodes themselves, especially when executed on large-scale static homogeneous WSNs, significantly impacts the energy consumption. Hence, it is assumed inappropriate for our subject of research. Additionally, a IDS is intended not to introduce weaknesses into a WSN. The distribution of IDSs requires by itself a increased level of trust in the communication and sensor nodes. However, many collaborative and distributed IDSs provide a promising basis to design a cooperative security framework integrating further components to collaborate.

### B. DOMINATING SETS AND DOMATIC PARTITIONS

To determine suitable static distributions of a fix number of security mean types intended to cooperate, local proximity is a key factor. The concept of dominating sets and domatic partitions (alternatively fall k-colouring [19]<sup>1</sup>) is well suited. In a dominating set, each node is either adjacent to a node of the set or included in it. If sets represent security mean types, such a partition ensures the local proximity in a network. Hence, a security mean type is either available on a selected node or a neighbouring node. A domatic partition of a graph is the partitioning of it into disjoint dominating sets. If for a graph and a given number of security means such a partition exists, local proximity is ensured. [20] states that the domatic partition problem that asks whether the nodes of a graph can be partitioned into  $k \in \mathbb{N}_{>3}$  dominating subsets is NP complete. Known applications of dominating sets exist in the field of wakeup scheduling for WSNs [21]-[26]. However, in wakeup scheduling applications, dominating sets do not need to be disjoint. The major concern in energy-saving wakeup scheduling schemes is that at least one node in a neighbourhood of each node has to be kept awake to ensure that it can wakeup surrounding nodes. On the contrary, our applications require disjoint partitions into dominating sets.

 $<sup>{}^{1}</sup>A$  graph colouring problem that determines whether a graph can be coloured with *n* colours so that in each node's neighbourhood all colours are present.

The term fractional domatic partition was introduced in [27]. This algorithm however determines a number of non-disjoint dominating sets. Conversely, we attempt to determine a fixed size partition of disjoint sets approaching dominating sets as far as possible. Therefore, we approach the definition based on desired criteria, as we will introduce in the following sections.

In [21], an approximation algorithm which tries to maximise the number of fractional domatic partitions in a graph to efficiently sleep schedule nodes is shown. Furthermore, there exist a multitude of publications towards the domatic number and domatic partition problem with regards to different approximations and solution for specialised graph types providing lower and upper bound assumptions of their computational complexity. In [28] a polynomial approximation algorithm estimating the lower and upper bounds of the domatic number on general graphs is presented. Additionally, [28] determines a greedy approximation algorithm for domatic partitions of graphs. The algorithm computes as many small disjoint dominating sets as possible to receive a partition of fixed size. Other attempts achieving more precise bounds for the domatic number and domatic partition problem have been executed on general graphs [29], [30] as well as special types of graphs, e.g. interval graphs [31] or RGGs [32]. [33] determines an approximation algorithm for domatic partitions on UDGs. The survey [34] discusses and summarises a large number of research results and solutions towards different dominating set problems and compares the performances and properties of different algorithms proposed.

We intend to calculate our static distributions of security means (partitioning schemes) analytically. The security means are distributed on nodes and not exchanged during runtime. Therefore, an optimal distribution is a key factor for the overall performance of the security framework. Furthermore, we have different requirements towards the partitioning compared to the distributions examined in sleep scheduling applications.

### C. GENERATORS FOR GRAPH MODELS OF WSNS

A lot of research is done regarding the generation of graphs as model for different types of networks. One of the first models for generating random graphs as network model is the Erdős-Rényi model [35] expressed by G(n, p). It is a popular way to construct Erdős-Rényi graphs. In this model, n labelled nodes are connected randomly. For all pairs of nodes, an edge is included with the probability p. Other popular models for random graph generators are the Barabási-Albert model [36] and the Watts-Strogatz model [12]. The Barabási-Albert model aims to create scale-free graphs as network models. Therefore, the degree distribution in the resulting graphs follows a power law. The Watts-Strogats model generates graphs with small-world properties which are characterised by a high clustering coefficient and a low average shortest path length between nodes. [37] reasons why RGGs are well suited as graph topology model for WSNs. In [38] the author first mentions similar graph models called "Random Plane Networks" as representation of wireless networks. The resulting graphs are closely related to UDGs. Those type

of graphs are most often the model of choice to represent WSNs. In [39] a model to generate WSNs that have a high probability to be connected as model for WSNs and ad hoc networks is introduced. To achieve the property connected with a high probability, the authors rely on a scheme that they call the proximity algorithm (PA). The PA places nodes iteratively on a finite plane. The first node is placed randomly within the generation plane. The following nodes are placed within radius r of the previously placed nodes. Even so, r is usually chosen larger than the distance in which two nodes are connected in a UDG, the likeliness of receiving a connected UDG using the PA increases significantly. A major downside of this approach is the likeliness for nodes in the graph to be highly clustered together. One of the most popular concepts for the generation of random graphs as model for wireless ad hoc, actuator and wireless sensor networks has been published in [40]. The publication introduces two types of algorithms to generate random UDGs. Centre node based algorithms are one type and acceptance/rejection based algorithms are the other. With centre node based algorithms, a node out of the previously placed nodes is chosen (centre) and the new node is placed in reach of the chosen centre. The paper presents four different algorithms. Each of them introduces different centre choosing strategies. The second type, acceptance/rejection based algorithms, works by iteratively choosing random node locations. The selected location is accepted or rejected based on given constraints. The authors propose three different algorithms to apply the acceptance/rejection based concept. The resulting graphs are called constrained connected random UDGs (C-CRUG). The term constrained reflects the circumstance that the placement is not completely random but constrained by the node positions of previously placed nodes. Moreover, the term connected means that the final result will only be accepted if the graph is connected.

In [40] the authors relied on three different constraints. The proximity constraint which is closely related to the PA by [39]. It ensures that each node is placed close to previously placed nodes increasing the likeliness for the resulting graph to be connected. Each node successive to the first node has to be placed within an approximated radius of previously placed nodes. The radius is estimated based on further desired graph properties. As with the PA, the radius constraining the node placement increases the likeliness of receiving islands of strongly clustered nodes. The actual radius used to decide whether two nodes in the graph are connected is determined as the  $\frac{N \cdot d_{avg}}{2}$  th shortest edge with N the number of nodes in the graph and  $d_{avg}$  the average node degree. Therefore, resulting graphs are not guaranteed to be connected. The second constraint used in [40] is the maximum degree constraint. It accepts the placement of a new node only if it does not increase the degree of the already placed nodes above a given maximum value. The third and last constraint was named the coverage constraint. With the coverage constraint, a new node location is only accepted if it extends the area that will be covered by the nodes of the graph sufficiently. Regarding

the proximity constraint [40], a minimal distance in between nodes equal to the  $\lambda$  in  $\lambda$ -precision graphs is considered. But the paper merely employs the distance to avoid that two nodes will be placed on the same coordinate instead of utilising  $\lambda$ for a better spatial node distribution. Hence, proposed centre node based algorithms from [40] are:

**Minimum Degree Proximity Algorithm (MIN-DPA):** It distributes nodes more uniformly while still maintaining connectivity. The first node is placed completely at random. Succeeding nodes are placed in the range of previously placed nodes with the lowest degree. In case there are multiple equally suitable contenders, all nodes get assigned a weighting scheme based on further criteria.

**Clustered Minimum Degree Proximity Algorithm** (**C-MIN-DPA**): Instead of distributing homogeneous nodes, this algorithm starts to distribute access points (APs). They are assumed to be connected first. The nodes will then be placed in close proximity to the APs, so they are connected to them.

Weighted Proximity Algorithm (WPA): This algorithm is similar to MIN-DPA but it considers all previously placed nodes as centres instead of just the ones with the lowest degree. To randomly select nodes, all nodes associated with a weight relative to their node degree. Therefore, nodes with a higher degree receive a smaller weight.

**Eligible Proximity Algorithm (EPA):** The nodes and their transmission ranges that serve as possible candidates for the location of the next node are selected by a given upper bound of the node degree. If the estimated node degree is larger than a given upper bound the placement of nodes is done according to WPA.

Proposed acceptance/rejection based algorithms are:

**Maximum Degree Proximity Algorithm (MAX-DPA):** The algorithm sets a maximum degree constraint per node. A random node position is generated uniformly. If the node satisfies the proximity constraint as well as the maximum degree constraint the new position is accepted.

**Coverage Algorithm 1 (CA1):** The first node is placed completely at random. Subsequent nodes, choose a random coordinate. Their position is validated by a coverage constraint checking if the selected region is already sufficiently covered by previously placed nodes.

**Coverage Algorithm 2 (CA2):** CA2 works similar to CA1 but with a stricter coverage constraint. The covered portion of the sensing area for a new node location is explicitly computed with regard of the previously placed nodes. If the portion of the sensing area gained by the new node location is

below a given threshold, the node location is rejected.

Our graph generator follows a different approach. We distribute nodes uniformly at random only constrained by a generation plane and a minimal distance in between nodes called  $\lambda$ -precision. Instead of using  $\lambda$  to prevent nodes from occupying the same spot as in [40], we apply it to improve their spatial distribution and control a number of graph properties. When distributing a number of sensor nodes with fixed sensing range given by radius  $r_{\text{sensing}}$ , it is often of interest to maximise the monitored area.

Therefore,  $\lambda$  should usually be set between the radius r<sub>sensing</sub>, a single sensor nodes sensing range and its transmission range  $r_{\rm tr}$  in which a sensor node is able to communicate. Choosing  $\lambda$  larger than the transmission range prevents nodes from communicating. The rings resulting from the two radii  $\lambda$  and  $r_{\rm tr}$  limit the maximum node degree of each node. The choice of  $\lambda$  and  $r_{tr}$  relative to each other and relative to the generation plane determines the probability that a randomly generated graph is connected. Even so, we distribute nodes in a unit square, the generation plane can have any shape. Therefore, our proposed generator is suitable to be further developed into a topology generator allowing distributions of sensor nodes in target environments. Additionally, we demonstrate that despite the flexibility in node placement, the local cluster coefficient and average node degree can be tailored to meet specific requirements precisely.

# **IV. DISTRIBUTION OF SECURITY MEANS**

The neighbourhood watch inspired security framework by [2] intends to distribute different security means in a WSN enabling an increased threat coverage while keeping the energy consumption at bay. To achieve such a distribution, sensor nodes need to instantiate a beneficial cooperation of security solutions. It is obvious that nodes are not capable to constantly run their security mean for neighbouring nodes as a service while ensuring their own longevity. Instead, they can execute security means in specialised patterns periodic patterns to detect malicious patterns and post-process security violations. The detection is solvable with a cooperative multilayer IDS approach, while the intrusion prevention preemptive and reactive requires further tools. Suitable candidates are lightweight trust-and-reputation systems [41], node isolation schemes [42], resilient recovery techniques for compromised nodes [43], [44], lightweight encryption schemes [45]. For the realisation of the security framework, following three assumptions have to be met:

- trusted communication between sensor nodes has been established
- WSN is static (nodes are immobile)
- attacker has no knowledge regarding the distribution of security means

We consider static distributions of security means. Meaning, sensor node carry pre-installed security means and are incapable to exchange or rotate their security mean. In the considered WSNs, we intend to distribute n different types

of security means. Hence, we contemplate it mandatory to ensure the availability of each type of security mean in the neighbourhood of each node if possible. Therefore, nodes have access to all security mean types applied to the network. A distribution of this kind is achievable in case each security mean type is either implemented on the observed node or on one of its neighbours. Therefore, we aim to ensure that the set of all nodes implementing the same security mean type in union with the set of all neighbours of those nodes results in a set containing all nodes of the network. Such a set is called a dominating set in graph theory. Considering the set of nodes implementing the same security mean as a set for all security means, we get n disjoint sets of nodes. Those sets are called dominating sets in graph theory. A partition of *n* disjoint dominating sets of nodes of a graph is called a domatic partition. The number of applied security mean types distributed in a network implies the number of necessary dominating sets. The maximum number of disjoint dominating sets per graph is called domatic number n. Choosing *n* larger than the domatic number of a graph, makes a partitioning in to n disjoint dominating sets impossible. Therefore, we introduce the term *n*-soft domatic partition. An *n*-soft domatic partition attempts to compute a best possible fit as compromise with regards to the model parameters. Another attempt to achieve an improved distribution of security means is the assumption to soften the neighbourhood term. So far, we are considering direct neighbourhoods (one-hop). Assuming multi-hop neighbourhoods, we are more likely to find an optimal partitioning as we later elaborate. We also discuss fix and workload-based distributions of multiple security means per node. Those approaches have currently limited practical applicability but can become relevant in the future. The partition scheme, introduced in this work, we name maximal/optimal *n*-soft domatic partition. Primarily, we choose to focus on distributing one security mean per node are the resource limitations and longevity of nodes. For this reason, we also focus on the one-hop neighbourhood in our analysis. A one-hop neighbourhood significantly limits the number of nodes depending on a security mean type and therefore inflicting an increased load to it. Viable alternative strategies are to consider multi-hop neighbourhoods allowing a more flexible rebalancing of node affiliations.

# V. OPTIMAL AND MAXIMAL N - SOFT DOMATIC PARTITIONS

An *n*-soft domatic partition describes the partitioning of a graph into *n* disjoint sets. While a domatic partition of size *n* is restricted to graphs with a domatic number greater-equal to *n*, an *n*-soft domatic partition is computable for graphs with a domatic number lower than *n*. We define two types of *n*-soft domatic partitions. Both types use different error terms to define either an optimal or a maximal *n*-soft domatic partition by minimising its respective error. An *n*-soft domatic partition of size *n* with nodes *V* of a graph G = (V, E) into disjoint sets

of nodes 
$$D_1, \ldots, D_n$$
 is defined as:

$$\mathbb{D}(G) = \{D_i \subseteq V \mid i = 1, \dots, n \land \bigcup_{D \in \mathbb{D}} D = V \land \bigcup_{\substack{D_1, D_2 \in \mathbb{D} \\ D_1 \neq D_2}} D_1 \cap D_2 = \emptyset\}$$
(12)

The definition of an n-soft domatic partition coincides with the definition of a regular partition of size n. After introduction of the terms optimal and maximal as additional conditions to the n-soft domatic partition, we define more specialised mathematical terms.

**Optimal** *n***-Soft Domatic Partition:** An *n*-soft domatic partition is called optimal iff missing coverages  $e_{\text{miss}\_\text{cov}}$  from Equation (13) is minimal. In consequence, the optimal *n*-soft domatic partition minimises the sum of missing coverages over all nodes.

**Maximal** *n*-Soft Domatic Partition: An *n*-soft domatic partition is maximal iff the number of incompletely covered nodes  $e_{\text{inc\_nodes}}$  defined in Equation (14) is minimal. Therefore, it is irrelevant whether N[v] of a node  $v \in V$  of graph G = (V, E) has one or multiple non-empty intersections with any set  $D \in \mathbb{D}$ .

We use the newly introduced terms to determine a distribution of n security mean types on sensor nodes of a WSN with a domatic number smaller than n. A maximal n-soft domatic partition ensures that the maximum number of nodes and its neighbourhood contains the full set of n security means. The optimal n-soft domatic partition guarantees that the number of missing coverages in a WSN is minimal. Hence, ensuring the sum of the absence of the number of security mean types in the inclusive neighbourhood of all nodes is minimal.

**Error Terms in Soft Domatic Partitions:** The definition of optimal and maximal *n*-soft domatic partitions is based on two error terms. Those will be evaluated in our empirical analysis. The missing coverages are defined as the sum of the *n* security mean types minus the security mean types present in the neighbourhood of a node N[v] in a graph G = (V, E) over all nodes  $v \in V$ :

$$e_{\text{miss\_cov}} = \sum_{v \in V} (n - |\{D| \forall u \in N[v] : \exists D \in \mathbb{D} : D \cap u \neq \emptyset\}|) \quad (13)$$

with the set of nodes utilising the same security mean type creating a partition D in the set of partitions  $\mathbb{D}$ .

In Fig. 3, we depict as example a graph with nodes of three colours magenta, blue, yellow. Each of those colours represents a set of nodes D within a partition  $\mathbb{D}$  of the given graph. All four nodes marked with a red ring contribute to the number of missing coverages. A node is fully covered if its inclusive neighbourhood contains nodes of all colours. In

Fig. 3, the number of missing coverages  $e_{miss\_cov}$  is 6. There are four incompletely covered nodes surrounded by a red ring. The blue node at the lower left corner of the graph lacks the coverage of a yellow and a magenta security mean in its neighbourhood. So, its contribution to the coverage error is 2. The same holds for the blue node at the lower right corner of the graph. Here, two security means (yellow and magenta) are missing. The yellow node directly above has no access to the magenta security mean. Its coverage error is 1. Finally, the yellow node marked with a red ring in the top line of the graph misses the magenta security mean. Resulting in a coverage error of 1. In total,  $e_{miss\_cov}$  results in 2+2+1+1=6.

The second error term is named incompletely covered nodes. Counting the number of nodes  $v \in V$  of G = (V, E) for which the number of distinct security means in N[v] is smaller than *n*:

$$e_{\text{inc\_nodes}} = \sum_{v \in V} f\left(n - |\{D| \forall u \in N[v] : \exists D \in \mathbb{D} : D \cap u \neq \emptyset\}|\right) \quad (14)$$

with 
$$f(x) = \begin{cases} 0, & x < 1\\ 1, & x \ge 1 \end{cases}$$
 (15)

Let us again illustrate an example by the graph in Fig. 3. The four nodes marked with a red ring are incompletely covered. Hence, they are missing one or several distinctly coloured nodes in their inclusive neighbourhood. In order to be completely covered by security means, a node needs to have access to all three colours (blue, magenta, yellow) within its direct neighbourhood. The error term  $e_{inc_nodes}$  identifies these nodes and sums up their occurrences. So, we obtain as result  $e_{inc_nodes} = 4$ .

In the worst case, for a graph G = (V, E) with V the set of nodes and E the set of edges is at most

$$\max_{e_{\text{miss\_cov}}} (G) = |V| \tag{16}$$

incompletely covered nodes and

$$\max_{e_{\text{inc\_nodes}}} (G) = (n-1) \cdot |V|$$
(17)

errors for a partition of size n, since each node has to be in at least one of the sets of the partition. An example for a worst case is the instance in which all nodes of a graph host the same security mean while the total number of required security means is higher (n > 1).

# A. DOMATIC PARTITION LP

To compute the domatic partition of size *n* of a given graph G = (V, E), we conceptualise a 0 - 1 LP without objective function. The LP returns either a feasible solution or terminate with the response that no feasible solution exists. In case a feasible solution exists, the assignments of the binary variables provide a feasible graph partitioning. Hence, the 0 - 1 LP determines a domatic partition of size *n*.

To construct a 0-1 LP, we need to define a number of variables and construct a set of constraints representing the

properties of a domatic partition. We define the variables  $x_i^{\nu} \in \{0,1\}$  of the underlying 0-1 LP. The upper index provides the identifier for the corresponding node  $v \in V$  and the lower index links to the partition i = 1, ..., n. For each node  $v \in V$ , there are exactly *n* variables, one for each partition. A value 1 of a variable  $x_i^{\nu}$  associates the node *v* with the set *i* of the partition. Otherwise, the value 0 indicates that node *v* is absent from the partition.

The first set of constraints we introduce ensures that each node has to be included in exactly one dominating set of the domatic partition:

$$\forall v \in V : \sum_{i=1}^{n} x_i^v = 1 \tag{18}$$

Moreover, we formalise that each node is either part of a dominating set or adjacent to one:

$$\forall v \in V, \ \forall i \in \{1, \dots, n\} : \sum_{w \in N[v]} x_i^w \ge 1$$
(19)

Hence, for all dominating sets of a domatic partition the intersection with the set of adjacent neighbours N[v] including the observed node v is not empty.

The final 0 - 1 LP without objective function reads as follows:

$$\begin{array}{ll} \forall v \in V : & \sum_{i=1}^{n} & x_{i}^{v} = 1 \\ \forall v \in V, \forall i \in \{1, \dots, n\} : & \sum_{w \in N[v]} & x_{i}^{w} \ge 1 \\ \forall v \in V, \forall i \in \{1, \dots, n\} : & x_{i}^{v} \in \{0, 1\} \end{array}$$

$$(20)$$

It determines whether a graph can be partitioned into an n-domatic partition. As a result it provides a domatic partition of the graph as solution. Hence, the LP solves a satisfiability problem stating whether a given graph can be partitioned into n disjoint dominating sets.

We can extend the LP as proposed in the previous section by allowing each node to implement  $k \in \mathbb{N}_{>0}$  different security means. To do so, it is only necessary to change the constraint from the Equation (18) to:

$$\forall v \in V : \sum_{i=1}^{n} x_i^v = k \tag{21}$$

In the context of WSNs, the resulting partitioning yields a distribution of *n* security mean types with *k* security mean types implemented per node *v* and all  $v \in V$ : |N[v]| = n if one exists.

Furthermore, we can apply a variable number of security means per node based on an estimation of their respective resource costs. To do so, we apply fixed costs  $m_i \in (0, 1]$  to each security mean i = 1, ..., n, a portion of the total available resources per node which w.l.o.g. is set to 1. As long as the available resources on a node are not exhausted, additional security means can be applied. The constraint from Equation (18) is modified as follows:

$$\forall v \in V : \sum_{i=1}^{n} m_i \cdot x_i^v = 1 \tag{22}$$

# B. OPTIMAL/MAXIMAL N - SOFT DOMATIC PARTITION LPS

Based on the LPs for the satisfiability conditions of domatic partitions from the preceding section, we introduce LPs for optimal and maximal *n*-soft domatic partitions. At first, it is necessary to drop the constraints from Equation (19). The constraints ensure that each set of the partition is a dominating set. For maximal and optimal *n*-soft domatic partitions of graphs with *n* greater than their domatic number, no partitioning into *n* disjoint dominating sets exists. Instead, we introduce an objective function minimising either the number of missing coverages (Equation (13)) or the number of incompletely covered nodes (Equation (14)) for optimal and maximal *n*-soft domatic partitions.

We start with Equation (13) to minimise the missing coverages. Therefore, we transform the counting of missing coverages into a more applicable form for construction of partitions. The objective function uses the previously defined function f in Equation (15). All identifiers and variables such as  $x_i^{\nu}$  and n previously introduced in the Equations (18) to (20) of the preceding subsection keep their semantics. The LP to determine an optimal n-soft domatic partition then reads as follows:

$$\max \sum_{\nu \in V} \sum_{i=1}^{n} f\left(\sum_{w \in N[\nu]} x_{i}^{w}\right)$$
  
s.t.  $\forall \nu \in V : \sum_{i=1}^{n} x_{i}^{\nu} = 1$  (23)  
 $\forall \nu \in V, \forall i \in \{1, \dots, n\} : x_{i}^{\nu} \in \{0, 1\}$ 

At first, we look at  $\sum_{w \in N[v]} x_i^w$ . The sum iterates over all  $w \in N[v]$ . It checks for each node v associated with set i whether a node of N[v] is included in the set i of the partition. The result is passed on to the function f from Equation (15). The function indicates whether at least one member of N[v] is linked to set i or no member of N[v] is included in set i with the values 1 and 0 respectively. Hence, the appearance of more than one node in N[v] included in the set i of the partition does not influence the optimisation result. The outer sums  $\sum_{v \in V} \sum_{i=1}^n f(\sum_{w \in N[v]} x_i^w)$  ensure that the value is determined for all combinations of nodes  $v \in V$  and sets i of the partition. By maximising the resulting value, we are minimising the number of missing coverages (Eq. (13)).

To compute the maximal *n*-soft domatic partition the objective function is adapted as follows:

$$\max \quad \sum_{v \in V} f\left(n^{-1} \cdot \sum_{i=1}^{n} f\left(\sum_{w \in N[v]} x_{i}^{w}\right)\right)$$
(24)

The term  $n^{-1} \cdot \sum_{i=1}^{n} f\left(\sum_{w \in N[v]} x_i^w\right)$  describes the portion of sets of the partition having at least one common member with the set N[v]. For the maximal *n*-soft domatic partition it only matters whether a node's neighbourhood N[v] has common members with all sets of the partition. Hence, we map the result to 0 or 1 and maximise the sum of those values. The LP applying this objective function minimises the number of incompletely covered nodes (Eq. (14)) by maximising the number of fully covered nodes.

Linear solvers are not able to solve objective functions with case distinctions directly. So, it is necessary to replace them. Therefore, we reformulate the LP to fit the standard form introduced in Equation (7).

To do so, we introduce a set of auxiliary variables and additional constraints:

$$\max \begin{array}{l} \max & \sum_{i=1}^{n} \sum_{v \in V} y_{i}^{v} \\ \text{s.t.} & \forall v \in V : \\ & \forall v \in V, \forall i \in \{1, \dots, n\} : \quad y_{i}^{v} \leq \sum_{w \in N[v]} x_{i}^{w} \\ & \forall v \in V, \forall i \in \{1, \dots, n\} : \quad x_{i}^{v}, y_{i}^{v} \in \{0, 1\} \end{array}$$

$$(25)$$

The first new set of constraints  $\forall v \in V$ ,  $\forall i \in \{1, ..., n\} : y_i^v \leq \sum_{w \in N[v]} x_i^w$  ensures that the auxiliary variable  $y_i^v$  is set to 1 if in N[v] exists a node included in set *i* of the partition. Therefore, if there are multiple nodes of N[v] in the set *i* of the partition it does not affect the outcome of our LP because  $y_i^v$  is a binary variable and cannot grow larger than 1. The resulting objective function maximises the sum of all  $y_i^v$ . Therefore, it replaces our auxiliary function *f*.

For the maximal *n*-soft domatic partition, we repeat the pattern applied to Equation (25) in similar fashion:

$$\max \sum_{v \in V} \sum_{i=1}^{v} x_i^v = 1$$
s.t.  $\forall v \in V : \sum_{i=1}^{n} x_i^v = 1$ 
 $\forall v \in V, \forall i \in \{1, \dots, n\} : y_i^v \leq \sum_{w \in N[v]} x_i^w$  (26)
 $\forall v \in V, \forall i \in \{1, \dots, n\} : z^v \leq y_i^v$ 
 $\forall v \in V, \forall i \in \{1, \dots, n\} : x_i^v, y_i^v \in \{0, 1\}$ 

Instead of summing up the  $y_i^v$  as the number of sets of the partition, the nodes of N[v] are included in, we only like to Again,  $y_i^v$  is 1 if N[v] incorporates at least one node of the set *i* of the partition. Additionally, we introduce the set of auxiliary variables  $z^v \in \{0,1\}$ . The constraint  $\forall v \in V, \forall i \in \{1,...,n\}: z^v \leq y_i^v$  and objective function ensure  $z^v$  is equal to the largest  $y_i^v$ . Hence, the LP minimise the number of incompletely covered nodes from Equation (14) by maximising the number of completely covered nodes.

The LP for the optimal as well as the maximal *n*-soft domatic partition can also be modified to minimise the number of missing coverages or incompletely covered nodes if a node incorporates more than one security mean. We have discussed two versions of this approach: Either by implementing a fix number of security means per node or by distributing different combinations of security means based on their individual estimated costs. If a node is allowed to implement a fix number of  $k \in \mathbb{N}_{>1}$  different security means, the constraint  $\forall v \in V : \sum_{i=1}^{n} x_i^v = 1$  changes to:

$$\forall v \in V : \sum_{i=1}^{n} x_i^v = k \tag{27}$$

Next, we apply security means (associated with sets *i* of the partition) based on the share of resources necessary per security mean  $m_i$ , available at each node  $v \in V$ . The constraint  $\forall v \in V : \sum_{i=1}^{n} x_i^v = 1$  has to be updated as follows:

$$\forall v \in V : \sum_{i=1}^{n} m_i \cdot x_i^v = 1$$
(28)

The resource costs over all security means form a vector  $\mathbf{m} \in \mathbb{R}^n$  with its components  $m_i \in (0, 1]$ . Without loss of

generality, the overall resources available for security means per node have been set to 1. Each value  $m_i$  represents the individual portion of costs caused for operating security mean *i* in relation to the total costs for all security means. The representation of necessary and available resources as a scalar is a simplification showing the feasibility of our LPs to take those into account.

### VI. $\lambda$ -PRECISION UDG GENERATOR

The algorithms we propose to distribute security means in favour of the neighbourhood watch inspired security framework for large-scale static homogeneous WSNs are NP hard. It is necessary to validate the computability of the algorithms on a large number of realistic WSN models. Since, we cannot pinpoint the exact influence of graph properties on the computation time of our partitioning algorithms, we examine it empirically. Computations on a large set of models enable us to study the relation between different graph properties and the computation time. To do so, we need a generator supplying is with a large variety and number of WSN graph models with desired properties.

With the growing demand and sizes of WSNs [46], the attention of potential attackers [47] increases as well. As consequence, more complex security [48] and communication protocols [49] are developed. The application of those protocols leads to an increasing power consumption which affects the available computational and energy resources for the actual tasks of nodes. Since nodes and their distribution are expensive and their failure can lead to the failure of the network, network operators are interested in maximising the potential lifetime of nodes and the networks. An attempt to deal with the higher demand in power are smart sleep scheduling schemes [50] and hop-by-hop communication strategies [51]. Additionally, there are many algorithms whose complexities exceed the deterministic polynomial time bound or are bound to higher polynomial degrees [52], [53]. For researchers to decide whether those algorithms can be solved analytically or bring the need of an approximation, empirical evaluations on WSN graph models with desired properties are necessary. To generate these models, we introduce a graph generator that creates  $\lambda$ -precision UDGs by distributing nodes randomly and uniformly in a unit square.

 $\lambda$ -precision UDGs have several advantages compared to ordinary UDGs. The  $\lambda$ -precision limits the node degree of each node in the graph. The limitation results from the size of the ring given by the radii  $\lambda$  and  $r_{tr}$  with  $0 < \lambda < r_{tr}$ . Nodes only connect (have common edges) to nodes within this ring, since each node has to have at least  $\lambda$  distance to other nodes in the network. Therefore, there is an upper limit of nodes that are able to connect. Choosing the  $\lambda$  distance and node number |V| so that a large portion of the area of the generation is covered ensures that the nodes are more evenly spaced out on the generation plane. Hence, it allows to control the variance of the local cluster coefficient. With regard to WSNs, evenly distributed nodes improve the area-wide monitoring.

### A. NODE DISTRIBUTION

To generate the graphs, we start with randomly and uniformly distributing nodes in a unit square with the constraint that two nodes have to have a minimal distance  $\lambda$  in between them. For an efficient computation, it is necessary to discretise the unit square. We do so, with a uniform grid size of 1000 times 1000. The grid size can be adapted as needed and is often chosen based on the computational limits and the intended graph properties as for example the number of nodes. In the implementation, we distributes the nodes iteratively. Each node occupies the grid coordinate of its centre and all grid coordinates within  $\lambda$  distance from it. For this purpose, each grid coordinate gets assigned a marker value. The marker indicates whether the coordinate is still available (0) or occupied (1). After a new node has been added, all surrounding marker values in  $\lambda$  distance are updated by setting them to 1. The coordinate for the centre of the succeeding nodes is randomly and uniformly selected from the non-occupied coordinates. The process is repeated until either no grid coordinates are available or the desired amount of nodes has been placed within the unit square.

### **B. GENERATOR SEEDS**

In order to create  $\lambda$ -precision UDGs with specific properties, it is essential to determine the input parameters (generator seeds) resulting in graphs with the desired properties. We use the following input parameters: number of nodes |V|, the pairwise minimal distance in between the nodes  $\lambda$  and the distance  $r_{\rm tr}$  up to which nodes are connected. For the empirical evaluation of random graphs, we compute for each parameter set a certain amount of graphs. After computing a set of graphs for chosen input parameters, we compare the properties with our target values. Depending on the outcome, we either save the result or adjust the input parameters. To do so, we apply a binary search separately for both parameters  $\lambda$  and  $r_{\rm tr}$ , starting with  $\lambda$ . Table 1 shows the resulting generator seeds to create random  $\lambda$ -precision UDGs with desired properties. As shown in Table 1 the target values are the medium total coverage of the generation plane  $\overline{A_{\text{coverage}}}$  and the medium average node degree deg<sub>avg</sub>.

The value of  $\overline{A_{coverage}}$  affects the probability of resulting random  $\lambda$ -precision UDGs to be connected  $P_{connected}$ . In addition, it ensures a low variance of the local cluster coefficient and an even coverage of the generation plane as we discuss in Subsection VI-C. Applying a binary search, we first approach the radius  $\lambda$  achieving an medium total coverage of the generation plane  $\overline{A_{coverage}}$  between 0.75 and 0.8. The coverage is determined numerically. After distributing nodes as described in the previous subsection, the relation between occupied grid coordinates grid size yields the total coverage of the generation plane  $A_{coverage}$ . Finally, the medium total coverage of the generation plane  $\overline{A_{coverage}}$  of all generated graphs for the input parameter set is computed.

Next, we determine the transmission range  $r_{tr}$  using a binary search until we reach a medium average node degree  $\overline{\text{deg}_{avg}}$ over all graphs obtained for the given input parameters. The final results of the computed generator seeds is shown in Table 1. To generate the graphs for the evaluation of our 0 - 1 LPs we will use the results from this table.

TABLE 1: Empirically determined seeds to generate graphs with an expected average node degree in between deg<sub>exp</sub> to deg<sub>exp</sub> +0.25 for a given number of nodes |V| and a desired medium total coverage of the generation plane  $\overline{A_{\text{coverage}}}$  from 75% to 80%. The values have been determined by generating repeatedly sets of 20 graphs for varying values of  $\lambda$  and  $r_{\text{tr}}$  until approaching the desired properties. The probability  $P_{\text{connected}}$  is the empirically determined likeliness of a graph to be connected for the given parameters. The results for  $\overline{A_{\text{coverage}}}$  and  $P_{\text{connected}}$  are the arithmetic mean values of 20 graphs of the determined input parameter combinations.

| V   | deg <sub>exp</sub> | λ        | $r_{\rm tr}$ | Acoverage | degavg | Pconnected |
|-----|--------------------|----------|--------------|-----------|--------|------------|
| 20  | 3                  | 0.210938 | 0.309375     | 0.771     | 3.057  | 0.857      |
| 20  | 4                  | 0.210938 | 0.363867     | 0.771     | 4.082  | 1.000      |
| 20  | 5                  | 0.210938 | 0.422900     | 0.771     | 5.228  | 1.000      |
| 20  | 6                  | 0.210938 | 0.453339     | 0.771     | 6.066  | 1.000      |
| 40  | 3                  | 0.143372 | 0.206250     | 0.796     | 3.223  | 0.866      |
| 40  | 4                  | 0.143372 | 0.235803     | 0.796     | 4.226  | 1.000      |
| 40  | 5                  | 0.143372 | 0.270884     | 0.796     | 5.203  | 1.000      |
| 40  | 6                  | 0.143372 | 0.293691     | 0.796     | 6.075  | 1.000      |
| 60  | 3                  | 0.113689 | 0.159375     | 0.780     | 3.081  | 0.555      |
| 60  | 4                  | 0.113689 | 0.183259     | 0.780     | 4.094  | 1.000      |
| 60  | 5                  | 0.113689 | 0.207903     | 0.780     | 5.080  | 1.000      |
| 60  | 6                  | 0.113689 | 0.229350     | 0.780     | 6.075  | 1.000      |
| 80  | 3                  | 0.095925 | 0.135937     | 0.751     | 3.196  | 0.550      |
| 80  | 4                  | 0.095925 | 0.153683     | 0.751     | 4.073  | 0.950      |
| 80  | 5                  | 0.095925 | 0.174016     | 0.751     | 5.017  | 1.000      |
| 80  | 6                  | 0.095925 | 0.193037     | 0.751     | 6.085  | 1.000      |
| 100 | 3                  | 0.086932 | 0.121875     | 0.781     | 3.248  | 0.600      |
| 100 | 4                  | 0.086932 | 0.137779     | 0.781     | 4.154  | 0.950      |
| 100 | 5                  | 0.086932 | 0.155897     | 0.781     | 5.161  | 1.000      |
| 100 | 6                  | 0.086932 | 0.169825     | 0.781     | 6.021  | 1.000      |
| 120 | 3                  | 0.078782 | 0.107812     | 0.783     | 3.150  | 0.368      |
| 120 | 4                  | 0.078782 | 0.122796     | 0.783     | 4.089  | 0.950      |
| 120 | 5                  | 0.078782 | 0.139347     | 0.783     | 5.111  | 1.000      |
| 120 | 6                  | 0.078782 | 0.154586     | 0.783     | 6.138  | 1.000      |
| 140 | 3                  | 0.071397 | 0.098437     | 0.758     | 3.000  | 0.100      |
| 140 | 4                  | 0.071397 | 0.113661     | 0.758     | 4.133  | 1.000      |
| 140 | 5                  | 0.071397 | 0.126504     | 0.758     | 5.022  | 1.000      |
| 140 | 6                  | 0.071397 | 0.140545     | 0.758     | 6.072  | 1.000      |
| 160 | 3                  | 0.066934 | 0.093750     | 0.755     | 3.203  | 0.100      |
| 160 | 4                  | 0.066934 | 0.106195     | 0.755     | 4.195  | 0.950      |
| 160 | 5                  | 0.066934 | 0.118888     | 0.755     | 5.168  | 1.000      |
| 160 | 6                  | 0.066934 | 0.129716     | 0.755     | 6.044  | 1.000      |
| 180 | 3                  | 0.062751 | 0.086719     | 0.750     | 3.096  | 0.200      |
| 180 | 4                  | 0.062751 | 0.098891     | 0.750     | 4.087  | 0.850      |
| 180 | 5                  | 0.062751 | 0.111389     | 0.750     | 5.121  | 1.000      |
| 180 | 6                  | 0.062751 | 0.122844     | 0.750     | 6.168  | 1.000      |
| 200 | 3                  | 0.060790 | 0.082031     | 0.790     | 3.103  | 0.157      |
| 200 | 4                  | 0.060790 | 0.094676     | 0.790     | 4.211  | 1.000      |
| 200 | 5                  | 0.060790 | 0.105122     | 0.790     | 5.124  | 1.000      |
| 200 | 6                  | 0.060790 | 0.116198     | 0.790     | 6.123  | 1.000      |
| 220 | 3                  | 0.056991 | 0.077344     | 0.755     | 3.039  | 0.250      |
| 220 | 4                  | 0.056991 | 0.088177     | 0.755     | 4.069  | 0.900      |
| 220 | 5                  | 0.056991 | 0.100885     | 0.755     | 5.234  | 1.000      |
| 220 | 6                  | 0.056991 | 0.110456     | 0.755     | 6.172  | 1.000      |
| 240 | 3                  | 0.054319 | 0.075000     | 0.772     | 3.156  | 0.200      |
| 240 | 4                  | 0.054319 | 0.084882     | 0.772     | 4.085  | 0.850      |
| 240 | 5                  | 0.054319 | 0.094884     | 0.772     | 5.086  | 1.000      |
| 240 | 6                  | 0.054319 | 0.104616     | 0.772     | 6.059  | 1.000      |
| 260 | 3                  | 0.052622 | 0.071484     | 0.779     | 3.103  | 0.200      |
| 260 | 4                  | 0.052622 | 0.081533     | 0.779     | 4.151  | 1.000      |
| 260 | 5                  | 0.052622 | 0.091546     | 0.779     | 5.135  | 0.950      |
| 260 | 6                  | 0.052622 | 0.101349     | 0.779     | 6.213  | 1.000      |
| 280 | 3                  | 0.050977 | 0.067969     | 0.777     | 3.012  | 0.100      |
| 280 | 4                  | 0.050977 | 0.078142     | 0.777     | 4.122  | 0.850      |
| 280 | 5                  | 0.050977 | 0.088195     | 0.777     | 5.175  | 1.000      |
| 280 | 6                  | 0.050977 | 0.096416     | 0.777     | 6.094  | 1.000      |
| 300 | 3                  | 0.048588 | 0.065625     | 0.765     | 3.028  | 0.100      |
| 300 | 4                  | 0.048588 | 0.075013     | 0.765     | 4.097  | 0.900      |
| 300 | 5                  | 0.048588 | 0.084900     | 0.765     | 5.166  | 1.000      |
| 300 | 6                  | 0.048588 | 0.093537     | 0.765     | 6.180  | 1.000      |

# C. CLUSTER COEFFICIENT AND DEGREE DISTRIBUTION

We show that the variance of the local cluster coefficient and the variance of the node degree distribution decreases with an increasing coverage of the generation plane. This allows to generate specific graphs and test the effect of those properties on the computation time of our partitions. We can assume that a graph contains an edge, or a small number of edges, whose removal would disconnect the graph into several larger connected components. In such cases, we can expect a decrease in computation time compared to a graph without such breaking points. Therefore, we expect that a low variance of the distribution of the node degrees provides information about an upper bound of the computation time. The portion of the covered area of the generation plane is directly linked to the combined choice of the number of nodes |V| and their minimal pairwise distance  $\lambda$  within the graph. To evaluate the behaviour of the interplay between the portion of the covered area of the generation plane and the variance of the node degree distribution as well as the variance of the local cluster coefficient we determine additional generator seeds. To do so, we first determine generator seeds for selected target values as in the previous section. We have chosen an expected average node degree  $\deg_{exp}$  of 4 and 5. The observed node numbers |V| are 100 and 200. For each of those combinations the expected covered area of the generation plane is set to the intervals  $\{[0.45, 0.5], [0.5, 0.55], [0.55, 0.6]$ [0.6, 0.65], [0.65, 0.7], [0.7, 0.75], [0.75, 0.8], [0.8, 0.85]. We exhibit the determined generator seeds in Table 2. The results indicate that the determined seeds maintain a high probability to create connected graphs even with a decreasing medium total coverage of the generation plane  $\overline{A_{\text{coverage}}}$ .

For our empirical analysis of the relation between the medium total coverage of the generation plane  $\overline{A_{\text{coverage}}}$  and the variance of the node degree distribution as well as the variance of the local cluster coefficient, we determine the parameters with the same binary search utilised in the previous subsection. By means of these parameters, we compute 40 sample graphs for each of the discussed target parameter combinations. The target parameters are number of nodes |V|, medium average node degree  $\overline{\deg_{avg}}$  and medium total coverage of the generation plane  $\overline{A_{coverage}}$ . A selection of 16 of the resulting uniformly and randomly determined  $\lambda$ -precision UDGs is displayed in Fig. 4.

The results of our evaluation are depicted in Fig. 5 and 6. The *x* coordinate for each data point is located at the lower value of the respective range representing the medium total coverage of the generation plane  $\overline{A_{\text{coverage}}}$  in both diagrams. Each data point represents the arithmetic mean over the variance of the local cluster coefficients and the list of node degrees per graph for a sample size of 40 graphs.

**D. METHODS FOR ADAPTATION OF GENERATED UDGS** Use case dependent adaptations of generated  $\lambda$ -precision UDGs can be necessary to satisfies certain requirements. Therefore, to specify the accuracy of the graph properties, we



have implemented methods to adapt the graphs resulting from our graph generator. Connectivity, occurrences of bridges or average node degree are properties, we have considered for adaptation. It is unlikely to receive a large randomly generated graph that meets exactly a set of desired properties based on selected input parameters. To improve quality, validity and precision of an evaluation using graphs, it is desirable that those graphs meet exact criteria. Certain properties are perhaps achievable solely by repeatedly generating graphs. However, such a process is tedious and time consuming, especially for large numbers of graphs.

**Connectivity:** Our approach to connect a graph consisting of several connected components uses the nearest neighbour attempt. The algorithm determines all pairs of nearest neighbour nodes between distinct connected components. For each iteration, the nearest neighbour pair with the shortest edge length (euclidean distance) is chosen and added as edge to the graph. Subsequently, all nearest neighbour pairs which in turn contain nodes from a single connected component inside the resulting graph are removed from the set. The last two steps are repeated until there is only one connected component in the graph.

Further, we assume that the occurrence of bridges in a graph model significantly affects the empirical test results and influences the evaluation of the computability of complex al-

TABLE 2: The seeds for our generator to test the behaviour of the variance of the local cluster coefficient and the variance of the node degree distribution subject to the total coverage of the generation plane have been computed as in Table 1. The abbreviation  $A_{exp\_cov}$  stands for the expected coverage area. It represents the coverage range for which we determine  $\lambda$  and  $r_{tr}$ . Therefore, the resulting coverage area  $A_{cov}$  of graphs generated with those parameters is likely to be within the specified range.  $\overline{A_{cov}}$  is short for  $\overline{A_{coverage}}$  and  $P_{conn}$  abbreviates  $P_{connected}$  according to Table 1.

| $A_{exp\_cov}$ | V   | deg <sub>exp</sub> | λ      | $r_{\rm tr}$ | $\overline{A_{\rm cov}}$ | deg <sub>avg</sub> | Pconn |
|----------------|-----|--------------------|--------|--------------|--------------------------|--------------------|-------|
| [0.45, 0.5]    | 100 | 4                  | 0.0732 | 0.135        | 0.498                    | 4.113              | 1.00  |
| [0.45, 0.5]    | 100 | 5                  | 0.0732 | 0.150        | 0.498                    | 5.019              | 1.00  |
| [0.45, 0.5]    | 200 | 4                  | 0.0503 | 0.093        | 0.463                    | 4.115              | 0.70  |
| [0.45, 0.5]    | 200 | 5                  | 0.0503 | 0.103        | 0.463                    | 5.087              | 1.00  |
| [0.5, 0.55]    | 100 | 4                  | 0.0747 | 0.135        | 0.516                    | 4.092              | 0.75  |
| [0.5, 0.55]    | 100 | 5                  | 0.0747 | 0.150        | 0.516                    | 5.024              | 1.00  |
| [0.5, 0.55]    | 200 | 4                  | 0.0525 | 0.093        | 0.531                    | 4.096              | 0.90  |
| [0.5, 0.55]    | 200 | 5                  | 0.0525 | 0.105        | 0.531                    | 5.209              | 0.95  |
| [0.55, 0.6]    | 100 | 4                  | 0.0761 | 0.135        | 0.561                    | 4.058              | 0.85  |
| [0.55, 0.6]    | 100 | 5                  | 0.0761 | 0.154        | 0.561                    | 5.240              | 1.00  |
| [0.55, 0.6]    | 200 | 4                  | 0.0535 | 0.093        | 0.565                    | 4.115              | 0.75  |
| [0.55, 0.6]    | 200 | 5                  | 0.0535 | 0.105        | 0.565                    | 5.223              | 1.00  |
| [0.6, 0.65]    | 100 | 4                  | 0.0791 | 0.135        | 0.630                    | 4.105              | 1.00  |
| [0.6, 0.65]    | 100 | 5                  | 0.0791 | 0.154        | 0.630                    | 5.213              | 1.00  |
| [0.6, 0.65]    | 200 | 4                  | 0.0543 | 0.093        | 0.601                    | 4.113              | 0.85  |
| [0.6, 0.65]    | 200 | 5                  | 0.0543 | 0.105        | 0.601                    | 5.179              | 1.00  |
| [0.65, 0.7]    | 100 | 4                  | 0.0805 | 0.135        | 0.658                    | 4.062              | 1.00  |
| [0.65, 0.7]    | 100 | 5                  | 0.0805 | 0.154        | 0.658                    | 5.144              | 1.00  |
| [0.65, 0.7]    | 200 | 4                  | 0.0566 | 0.093        | 0.668                    | 4.147              | 0.85  |
| [0.65, 0.7]    | 200 | 5                  | 0.0566 | 0.105        | 0.668                    | 5.185              | 1.00  |
| [0.7, 0.75]    | 100 | 4                  | 0.0820 | 0.135        | 0.704                    | 4.119              | 0.90  |
| [0.7, 0.75]    | 100 | 5                  | 0.0820 | 0.154        | 0.704                    | 5.113              | 1.00  |
| [0.7, 0.75]    | 200 | 4                  | 0.0589 | 0.093        | 0.732                    | 4.131              | 0.90  |
| [0.7, 0.75]    | 200 | 5                  | 0.0589 | 0.105        | 0.732                    | 5.182              | 1.00  |
| [0.75, 0.8]    | 100 | 4                  | 0.0878 | 0.135        | 0.797                    | 4.092              | 1.00  |
| [0.75, 0.8]    | 100 | 5                  | 0.0878 | 0.157        | 0.797                    | 5.238              | 1.00  |
| [0.75, 0.8]    | 200 | 4                  | 0.0597 | 0.093        | 0.759                    | 4.148              | 0.95  |
| [0.75, 0.8]    | 200 | 5                  | 0.0597 | 0.105        | 0.759                    | 5.163              | 1.00  |
| [0.8, 0.85]    | 100 | 4                  | 0.0878 | 0.135        | 0.800                    | 4.125              | 1.00  |
| [0.8, 0.85]    | 100 | 5                  | 0.0878 | 0.154        | 0.800                    | 5.050              | 1.00  |
| [0.8, 0.85]    | 200 | 4                  | 0.0617 | 0.093        | 0.815                    | 4.120              | 1.00  |
| [0.8, 0.85]    | 200 | 5                  | 0.0617 | 0.105        | 0.815                    | 5.135              | 1.00  |



 $\lambda$  (left to right): 0.0504, 0.0536, 0.0566, 0.0597

FIGURE 4: As example for the resulting  $\lambda$ -precision UDGs shown per row are from left to right generated for  $A_{coverage}$  of the ranges [0.45, 0.5], [0.55, 0.6], [0.65, 0.7] and [0.75, 0.8] respectively.

gorithms. To validate this hypothesis, we provide an algorithm allowing to identify and to remove bridges. The result is a connected, bridge-free graph that serves as representation of large-scale static homogeneous WSNs. To identify possible bridges in our  $\lambda$ -precision UDGs, our generator utilises the NetworkX library. Our general algorithm selects one of the identified bridges. Each node in the bridge indicates one of the bridge connected components. Thus, we determine a new edge that connects both components which in turn do not include either of the nodes of the bridge. Subsequently, we start over with the next bridge connecting two remaining bridge-connected components. The algorithm repeats the process until there are no more bridge-connected components left. A special case that needs to be treated before running the general algorithm is the appearance of bridge paths. We treat those first to prevent the general algorithm from infinitely looping. In such a case, we start at one end of the bridge path *P* incorporating the nodes  $v_s, v_{s+1}, \ldots, v_{s+k}$  and the edges  $\{\{v_s, v_{s+1}\}, \{v_{s+1}, v_{s+2}\}, \dots, \{v_{s+k-1}, v_{s+k}\}\}$  of the graph G = (V, E). Starting at  $v_s$  of the bridge path, we add an edge to the graph from  $v_s$  to the next but one node  $v_{s+2}$ . This procedure has to be repeated for each node except the



FIGURE 5: The mean of the variance of the local cluster coefficients tends to decrease along with increasing  $\overline{A_{\text{coverage}}}$  leading to more homogeneously distributed nodes with larger pairwise distances. A sample size of 40 graphs per data point has been utilised. This sample size balances the expressivity of the decrease trend with the computational effort for parameterised graph generation.



FIGURE 6: The mean of the variance of the node degree distribution mostly diminishes subject to a growing  $\overline{A_{coverage}}$ . This behaviour results in graphs that can be better employed for *n*-soft domatic partitions in a certain range for *n*. Again, a sample size of 40 graphs per data point has been utilised which implies some minor local fluctuations.

nodes  $v_{k-1}$  and  $v_k$ . After applying this procedure, all bridge paths have been eliminated from the graph and the general algorithm to remove the bridges of the graph can be executed.

Average Node Degree: The algorithm will remove edges from the graph until a desired average node degree has been achieved. We have chosen the edge length as decisive property to select the edges to be removed, since in WSNs a connection between nodes that are further apart is less likely. To do so, the

14

algorithm selects edges either based on their length starting with the longest, randomly with the probability for an edge to be removed weighted by their respective length as well as a given exponent or simply at random. As additional conditions, we can exclude edges whose removal causing the graph to be disconnected or create bridges in it.

#### VII. EMPIRICAL TEST SETUP

To evaluate the computability of optimal and maximal nsoft domatic partitions for reasonably sized large-scale static homogeneous WSNs, we outline the details of our empirical test setup. The corresponding graphs are created by the proposed  $\lambda$ -precision UDG generator using the seeds depicted in Subsection VI-B and the associated Table 1. We have chosen graphs with a number of nodes |V| starting from 20 to 300 in steps of 20. Only connected  $\lambda$ -precision UDGs created by our graph generator are accepted in our test setup. In case a generated graph is not connected, we discard it and repeat the generation process for the given parameters until the desired number of connected  $\lambda$ -precision UDGs has been reached. After successfully generating 20 connected graphs for each row of parameter combinations in Table 1, we duplicate the complete set of graphs once for a second test setup. The original set of graphs  $SG_1$  is then adapted to approach the expected average node degree degen by successive removal of edges. The algorithm used to adapt the graphs and to reach the desired average node degree is described in Subsection VI-D. To adjust the average node degree, we take the squared edge length of each edge that does not disconnect the graph as weight. The squaring gives longer edges a higher priority to be selected in the process. Then, edges are removed iteratively and by chance based on their respective given weight until the average node degree degays reaches the desired expected average node degree degexp. The graphs in the duplicated set  $SG_2$  are modified by removing all bridges as described in Subsection VI-D. Afterwards, we ensure that the deg<sub>exp</sub> in the table row associated with the graph is reached as described for  $SG_1$  but without the risk of creating new bridges. The set of graphs  $SG_2$  is created to evaluate whether small topological properties like for a graph to be bridge-free in our given set of graphs directly affects the computability or quality of results of our partitioning schemes. Finally, we compute for all graphs the optimal and maximal *n*-soft domatic partitions for  $n \in \{3, 4, 5\}$ . For this purpose, the 0-1 LPs have been implemented using Pyomo [10] and they are computed using the mathematical programming solver Gurobi [11]. In the last step, we evaluate the results via Python. Therefore, we track the wall-clock times given by Gurobi. In addition, we count the number of missing coverages  $e_{\text{miss}\_cov}$  introduced in Equation (13) as well as the incompletely covered nodes  $e_{inc nodes}$  expressed in Equation (14). The time limit for Gurobi to solve a given LP on a given graph is set to 1200 seconds on a system with two Intel® Xeon® Gold 6248R as central processing units and 256 GB of random access memory.

### **VIII. RESULTS AND EVALUATION**

Here, we evaluate the computation results of the optimal and maximal *n*-soft domatic partitions with  $n \in \{3, 4, 5\}$  and for 2400 different  $\lambda$ -precision UDGs divided into two test sets  $SG_1$  and  $SG_2$  as described in the previous section.

First, we start with solely discussing the results computed on  $SG_1$ . In Fig. 7, we evaluate the median of the computation time of the optimal 3, 4 and 5-soft domatic partitions in dependence on the number of nodes |V| of the given graphs. The colours of the respective curves represent the expected average node degree of the given graphs. The dotted lines in between the drawn data points are added exclusively to improve the readability of the plots.

The plot in Fig. 7 that is showing the optimal 3-soft domatic partition illustrates a comparatively steady increase of the median of the computation time with increasing graph sizes as expected. For the 4-soft domatic partition, we can see a deviation compared to the first plot.

While the graphs with an expected degree of 3, 5 and 6 are solved in negligible time, the partitioning for graphs with an expected degree of 4 takes significantly longer. There are a number of different possible explanations to this behaviour. One could expect that with increasing or decreasing average node degrees in a graph, the time to partition the graph also increases or decreases steadily and monotonously. Instead, we can register a significant growth of the median of the computation time only for a partition size of 4. An assumption for the behaviour of the curves is that graphs of average node degree 3 are easier to partition because the number of possibilities to assign nodes to a partition that improves the final result are limited. For graphs with a average node degree of 5 or 6, it can be argued that it is easier to find an optimal partitioning because only a limited number of nodes affect the final result. Therefore, the linear program also finds an optimal solution much faster. The diagram at the bottom of Fig. 7 displaying the median of the computation time results from the determination of the optimal 5-soft domatic partition. Here, we see another unexpected course of the curve. First, for average node degrees of 4, 5 and 6 the curve displays an increase in regards of the median of the computation time with an increasing number of nodes in the graphs but it drops for an average node degree of 5 and 6 again for one measuring point to jump back up directly at the next. A possible explanation is that the behaviour is caused by the limited size of 20 graphs per measuring point. Complementary, even slight changes in the number of optimal and non-optimal solutions cause the median to jump significantly. The non-optimal solutions emerge by the time limit of 1200 seconds per computation. A third explanation is that further topological properties of the graphs which we have not evaluated so far have an effect on the computation time.

Fig. 8 shows the results for the computation of the maximal 3, 4 and 5-soft domatic partitions of  $SG_1$ . The diagrams are structured in the same way as the diagrams from Fig. 7. The results in this figure are also subject to empirical fluctuations, particularly due to the limited number of test cases.



FIGURE 7: Test results of the median of the computation time in seconds *s* subject to the number of nodes |V| of given  $\lambda$ -precision UDGs necessary to determine optimal *n*-soft domatic partitions within a time limit of 1200 *s*.



FIGURE 8: Test results of the median of the computation time in seconds *s* necessary to determine maximal *n*-soft domatic partitions in dependence of the number of nodes |V| of  $\lambda$ -precision UDGs within a time limit of 1200 *s*.

The topmost diagram of Fig. 8 displays the results of the maximal 3-soft domatic partition. It shows that the median of the computation time increases with an increasing number of nodes in the graph. Furthermore, we can see that the increase of the average node degree comes with a decrease of the median of the computation time. This can be a consequence of the decreasing number of nodes that reach optimality and therefore contribute to the optimality result of the LPs. A similar effect becomes visible in the results of the computation of the maximal 4-soft domatic partition in Fig. 8 as well. While for graphs with an average node degree of 3, the LPs can be solved optimally in relatively low time because only a small number of nodes contributes to the optimality result. For graphs with an average node degree of 4, 5 and 6, we can again see a decrease of the median of the computation time along with an increase of the average node degree. With a larger empirical variation, we can see in the plot of the results of the maximal 5-soft domatic partitions of Fig. 8 that now for graphs with an average node degree of 5, the median of the computation time behaves similar to the median of the computation time of graphs with an average node degree of 3 for maximal 4 as well as 5-soft domatic partitions. In general, we see that for graphs with sufficiently large average node degrees subject to the partition size, the median of the computation time increases. The number of nodes in a graph also increases with the median of the computation time.

In Table 3, we compare and evaluate the cases in which for the given test setup and the set of graphs  $SG_1$  and for the given set of parameters at least one solution has been computed optimally and one non-optimally within the given time limit for either optimal or maximal *n*-soft domatic partitions. Even so, we compare results which have been computed for different graphs and for each parameter combination, we set up only a set of 20 graphs. The table reveals that the nonoptimal results are not significantly worse than the optimal results. In some cases, non-optimal results appear to be better than optimal results. This is caused by the different graphs on which we computed the results. Additionally, the small sample set and the unbalanced size of the division of the set into two sets for optimal and non-optimal solutions contributes to the empirical fluctuation in the results.

To compare the results of the maximal and optimal n-soft domatic partitions, we evaluate Fig. 9 in which we reflect the number of incompletely covered nodes as result of the computation of the maximal and optimal n-soft domatic partition. The dotted and dashed lines within the diagrams again only contribute to the readability and are not associated with computed data or interpretations.

In Fig. 9, we can recognise in the diagrams that in most cases the maximal n-soft domatic partition performs on average only slightly better than the optimal n-soft domatic partition. Furthermore, the Table 3 reveals that in most cases the number of solutions determined to optimality within the given time limit #opt is lower for the maximal than for the optimal n-soft domatic partition.

For a final comparison of the performance of the solu-



FIGURE 9: Arithmetic mean of the number of incompletely covered nodes in optimal and maximal *n*-soft domatic partitions subject to the number of nodes |V| of the given  $\lambda$ -precision UDGs of optimal *n*-soft domatic partitions within a time limit of 1200 *s*.

tions for maximal and optimal *n*-soft domatic partitions, we determine the relative mean of the results for the optimal and maximal *n*-soft domatic partition for the graphs in  $SG_1$ . The mean of the number of missing coverages  $e_{miss\_cov}$  with respect to the maximum number of missing coverages  $max_{miss\_cov}(G)$  for all graphs  $G \in SG_1$  and their computed partitioning of the optimal *n*-soft domatic partition arises to  $\overline{P_{miss\_cov}} = 23.72\%$ . Therefore, on average the number of missing coverages  $e_{miss\_cov}$  of the optimal *n*-soft domatic partition for our test setup and for the set of graphs  $SG_1$  is 23.72% lower compared to the maximal *n*-soft domatic partition. The same comparison for the maximal *n*-soft domatic partition yields  $\overline{P_{inc\_nodes}} = 1.11\%$ . This means that

TABLE 3: Results for parameter combinations of expected average node degree  $\deg_{exp}$ , partition size *n* and number of nodes |V| for which at least one optimal and non-optimal solution has been determined within the set time limit. The column #opt shows the number of solutions that have been solved to optimality. The other columns show the mean of the number of missing coverages as well as the number of incompletely covered nodes for optimal and non-optimal solutions.

| deg <sub>exp</sub> | п | V   | $e_{\text{miss cov}}^{\text{non_optimal}}$ | $e_{\text{miss cov}}^{\text{optimal}}$ | $e_{inc.nodes}^{non_optimal}$ | $e_{inc,nodes}^{optimal}$ | #opt |
|--------------------|---|-----|--|--|-------------------------------|---------------------------|------|
|                    |   |     | optimal n-s                                | soft domatic                           | partition                     |                           |      |
| 4                  | 4 | 180 | 96.00                                      | 81.74                                  | 70.00                         | 62.47                     | 19   |
|                    |   | 200 | 75.25                                      | 79.50                                  | 60.00                         | 61.88                     | 16   |
|                    |   | 220 | 98.14                                      | 105.85                                 | 76.86                         | 82.23                     | 13   |
|                    |   | 240 | 101.54                                     | 102.71                                 | 80.46                         | 80.71                     | 7    |
|                    |   | 260 | 107.88                                     | 105.00                                 | 84.56                         | 78.25                     | 4    |
|                    |   | 280 | 123.00                                     | 117.67                                 | 97.71                         | 93.67                     | 3    |
|                    |   | 300 | 134.56                                     | 127.00                                 | 105.89                        | 99.50                     | 2    |
| 4                  | 5 | 160 | 178.00                                     | 175.63                                 | 115.00                        | 112.21                    | 19   |
|                    |   | 180 | 200.00                                     | 202.78                                 | 126.00                        | 130.17                    | 18   |
|                    |   | 200 | 212.47                                     | 219.20                                 | 142.00                        | 141.20                    | 5    |
|                    |   | 220 | 257.00                                     | 251.27                                 | 163.80                        | 160.53                    | 15   |
|                    |   | 240 | 267.60                                     | 274.40                                 | 175.33                        | 176.40                    | 5    |
|                    |   | 260 | 287.11                                     | 295.00                                 | 189.06                        | 191.50                    | 2    |
|                    |   | 280 | 320.33                                     | 313.40                                 | 208.07                        | 206.40                    | 5    |
|                    |   | 300 | 345.47                                     | 334.33                                 | 224.88                        | 218.00                    | 3    |
| 5                  | 5 | 120 | 76.33                                      | 75.64                                  | 54.89                         | 54.82                     | 11   |
|                    |   | 140 | 94.69                                      | 91.50                                  | 67.94                         | 64.00                     | 4    |
| 6                  | 5 | 140 | 53.00                                      | 45.53                                  | 42.00                         | 34.21                     | 19   |
|                    |   | 160 | 52.45                                      | 54.33                                  | 41.18                         | 39.67                     | 9    |
|                    |   | 180 | 54.67                                      | 51.50                                  | 41.67                         | 39.71                     | 14   |
|                    |   | 200 | 61.43                                      | 56.67                                  | 48.57                         | 43.67                     | 6    |
|                    |   | 220 | 63.78                                      | 54.50                                  | 49.94                         | 44.00                     | 2    |
|                    |   | 240 | 76.47                                      | 69.00                                  | 59.84                         | 53.00                     | 1    |
|                    |   |     | maximal n-                                 | soft domatic                           | partition                     |                           |      |
| 4                  | 4 | 180 | 218.00                                     | 218.63                                 | 55.00                         | 55.19                     | 16   |
|                    |   | 200 | 204.57                                     | 220.46                                 | 51.43                         | 55.46                     | 13   |
|                    |   | 220 | 264.33                                     | 288.35                                 | 66.67                         | 72.65                     | 17   |
|                    |   | 240 | 276.92                                     | 284.63                                 | 69.67                         | 71.63                     | 8    |
|                    |   | 260 | 289.94                                     | 289.75                                 | 73.06                         | 73.00                     | 4    |
|                    |   | 280 | 345.38                                     | 324.92                                 | 86.88                         | 81.75                     | 12   |
|                    |   | 300 | 364.19                                     | 349.75                                 | 91.75                         | 88.00                     | 4    |
| 4                  | 5 | 160 | 490.00                                     | 502.00                                 | 98.67                         | 100.65                    | 17   |
|                    |   | 180 | 573.00                                     | 585.67                                 | 115.00                        | 117.56                    | 18   |
|                    |   | 200 | 594.73                                     | 618.56                                 | 119.27                        | 123.89                    | 9    |
|                    |   | 220 | 741.00                                     | 735.06                                 | 148.75                        | 147.44                    | 16   |
|                    |   | 240 | 742.78                                     | 774.91                                 | 149.00                        | 155.27                    | 11   |
|                    |   | 260 | 796.83                                     | 811.29                                 | 160.00                        | 162.64                    | 14   |
|                    |   | 280 | 891.89                                     | 905.55                                 | 178.78                        | 181.55                    | 11   |
|                    |   | 300 | 984.50                                     | 976.78                                 | 197.50                        | 195.89                    | 18   |
| 5                  | 4 | 300 | 133.50                                     | 125.28                                 | 33.50                         | 31.44                     | 18   |
| 5                  | 5 | 80  | 160.00                                     | 151.16                                 | 32.00                         | 30.26                     | 19   |
|                    |   | 100 | 180.27                                     | 172.00                                 | 36.09                         | 34.44                     | 9    |
|                    |   | 140 | 273.95                                     | 270.00                                 | 54.84                         | 54.00                     | 1    |
| 6                  | 5 | 100 | 95.00                                      | 106.32                                 | 19.00                         | 21.26                     | 19   |
|                    |   | 120 | 105.00                                     | 110.53                                 | 21.00                         | 22.11                     | 19   |
|                    |   | 140 | 147.50                                     | 125.63                                 | 29.50                         | 25.13                     | 16   |
|                    |   | 160 | 161.15                                     | 155.71                                 | 32.23                         | 31.14                     | 7    |
|                    |   | 180 | 163.33                                     | 155.36                                 | 32.67                         | 31.07                     | 14   |
|                    |   | 200 | 190.29                                     | 168.33                                 | 38.07                         | 33.67                     | 6    |
|                    |   | 220 | 199.44                                     | 187.50                                 | 39.89                         | 37.50                     | 2    |

on average the number of incompletely covered nodes for the maximal n-soft domatic partition is 1.11% lower compared to the optimal n-soft domatic partition. In Table 3, absolute values are shown that give an impression on the behaviour of the number of incompletely covered nodes and the number missing coverages resulting from the maximal and optimal n-soft domatic partitions.

For graphs in  $SG_2$ , we adapted the graphs from  $SG_1$  to be bridge-free. Our expectation was that this property has a significant impact on the computation time and on the quality of results regarding the number of missing coverages and incompletely covered nodes. Despite our expectations, the results yield that there exists no notable difference between the quality of results and the computation time. Our simulation case studies demonstrate that the elimination of bridges does not imply a significant effect on the computation time necessary to obtain optimal and maximal *n*-soft domatic partitions. The same holds for the achieved degree of optimality expressed by the number of incompletely covered nodes and by the number of missing coverages.

For most graphs, we have been able to determine the optimal and maximal *n*-soft domatic partitions to optimality. Additionally, the results have shown that non-optimal solutions are still close to optimality in most cases. While the results of the optimal *n*-soft domatic partitions exhibit a relatively low number of incompletely covered nodes, the number of missing coverages tends to grow fast for maximal *n*-soft domatic partitions in contrast. To make matters worse, the evaluation has shown that for the maximal n-soft domatic partition, we were unable to achieve optimality throughout computation even for smaller graph sizes. All together, the tests revealed that for most large-scale static homogeneous WSNs, the computation of maximal and optimal *n*-soft domatic partitions is possible and yields an optimal or almost optimal solution.

# IX. CONCLUSION AND FUTURE PROSPECTS

In this paper, we determined a distribution of security means based on the concept of a neighbourhood watch introduced by Langendörfer [2]. The concept aims to maximise the spectrum of security threats a large-scale static homogeneous WSN can detect or avert while minimising the load that will be put on individual nodes. To develop a complex security framework of this kind, there are several steps that have to be taken. Here, we introduced a graph partitioning scheme for the node distribution that is used in a different fashion for sleep scheduling schemes to minimise the energy usage of sensor nodes in WSNs. While sleep scheduling themes allow partitioning schemes that determine non-disjoint minimal dominating sets, we were looking for a partition that creates disjoint partitions that approximate the definition of dominating sets. Therefore, we defined two terms, the number of missing coverages and the number of incompletely covered nodes. To determine the partitions based on those terms, we introduced two 0 - 1 LPs for the maximal *n*-soft domatic partition and for the optimal *n*-soft domatic partition. Furthermore, we proposed several variations of those LPs allowing advanced distributions of security means that fit to the needs of differently equipped WSNs and to different levels of security threats. Since 0 - 1 LPs with objective functions are known to be NP hard, we designed a test setup to test the computability on graphs as representation for large-scale static homogeneous WSNs. This also implied the need for a suitable graph generator that enables to create realistic WSN models. Furthermore, it was necessary to control the resulting graph properties via the input parameters, so that the generator will produce different graphs with similar properties. Our graph generator aims at the creation of connected graphs as far as possible by purposive construction from the beginning. This feature avoids expensive trial-and-error strategies by iterating over a large number of insufficient graphs. Along with algorithmic design, we had to cope with the requirement that the constructive generation of connected graphs does not interfere with the desired uniform node distribution. As a result, we developed a new graph generator for  $\lambda$ -precision UDGs introduced in this publication. Its Python source code is available from the first author upon request. Additionally, further major properties we are able to control to some extent solely via the input parameters are the average node degree, the local clustering coefficient and the general coverage of the generation plane. Beyond, we provide several methods to further adapt the resulting graphs while maintaining their characteristics as representations of WSNs.

To evaluate the introduced LPs, we introduced a generator for  $\lambda$ -precision UDGs. The generator enabled us to evaluated which parameters affect the computation time at most by providing appropriate graphs. Our results have shown that in most cases the computation time is bound to the number of nodes in the graph, to the average node degree and to the desired partition size. Nonetheless, there have been some cases in which further topological properties of the graph affected the computation time significantly. To draw a final conclusion whether the computation time is mostly bound to the enumerated properties will take the need of additional tests. For now, we conclude that those properties provide very good information about the general runtimes one has to expect. Additionally, we have shown that the non-optimal solutions are almost as good as the optimal solutions, so that they also yield good distributions for given security means.

We have presented a number of variations towards the 0-1 LPs allowing distributions of a fixed number of security means per node and even distributions based on the performance cost of each security mean. The latter one allows to distribute varying numbers of security means per node based on their individual resource requirements. Those LPs have to be tested regarding to their computability as well. Our future work will address following steps:

- · determine suitable security means or adapt existing ones
- define an overall communication and security scheme that potentially considers
  - -- exchange of state vectors in between sensor nodes

- -- methods for intrusion detection
- -- the provision of security means in a software as a service fashion

The selection of suitable security means can in a final step than be modelled to fit the needs of an individual WSN following the concepts of the "Cooperation based Attack Defence Resource Trees" as proposed in [2]. Our graph generator is suited for adaptation to determination of automatic node distributions for given topologies. Those adaptations include the consideration of obstacles and elevation profiles as well as node capabilities. Even in arbitrary formed areas, the generator in its present version is able to automatically find suitable node distributions to achieve desired coverages. Only if coverages for a set of given sensor nodes with limited capabilities are technically not achievable, it will take manual intervention to limit the given size of the area to observe. In the end, those coverages are bound to the transmission range and to the power of sensor nodes as well as to the number of available sensor nodes.

### REFERENCES

- Rong Jiang, Jun Luo, and Xiaoping Wang. An attack tree based risk assessment for location privacy in wireless sensor networks. In 2012 8th International Conference on Wireless Communications, Networking and Mobile Computing, pages 1–4. IEEE, 2012.
- [2] Peter Langendörfer. Security engineering for cyber physical systems. Proc. 22nd EUROMICRO Conference on Digital System Design and Software Engineering and Advanced Applications - Session on Work in Progress (Euromicro DSD & SEAA 2019), 2019.
- [3] Steffen Peter and Peter Langendörfer. Tool-supported methodology for component-based design of wireless sensor network applications. In 2012 IEEE 36th Annual Computer Software and Applications Conference Workshops, pages 526–531. IEEE, 2012.
- [4] Alex Ramos, Marcella Lazar, Raimir Holanda Filho, and Joel JPC Rodrigues. Model-based quantitative network security metrics: A survey. IEEE Communications Surveys & Tutorials, 19(4):2704–2734, 2017.
- [5] Alex Ramos, Breno Aquino, Marcella Lazar, Raimir Holanda Filho, and Joel JPC Rodrigues. A quantitative model for dynamic security analysis of wireless sensor networks. In GLOBECOM 2017-2017 IEEE Global Communications Conference, pages 1–6. IEEE, 2017.
- [6] Alex Ramos, Marcella Lazar, Raimir Holanda Filho, and Joel JPC Rodrigues. A security metric for the evaluation of collaborative intrusion detection systems in wireless sensor networks. In 2017 IEEE international conference on communications (ICC), pages 1–6. IEEE, 2017.
- [7] Imran Khan, Fatna Belqasmi, Roch Glitho, Noel Crespi, Monique Morrow, and Paul Polakos. Wireless sensor network virtualization: A survey. IEEE Communications Surveys & Tutorials, 18(1):553–576, 2015.
- [8] Richard M Karp. Reducibility among combinatorial problems. In Complexity of computer computations, pages 85–103. Springer, 1972.
- [9] Aric Hagberg, Pieter Swart, and Daniel S Chult. Exploring network structure, dynamics, and function using networkx. Technical report, Los Alamos National Lab.(LANL), Los Alamos, NM (United States), 2008.
- [10] William E Hart, Jean-Paul Watson, and David L Woodruff. Pyomo: modeling and solving mathematical programs in python. Mathematical Programming Computation, 3(3):219–260, 2011.
- [11] Gurobi Optimization, LLC. Gurobi Optimizer Reference Manual, 2022.
- [12] Duncan J Watts and Steven H Strogatz. Collective dynamics of 'smallworld'networks. Nature, 393(6684):440–442, 1998.
- [13] Himali Saxena, Chunyu Ai, Marco Valero, Yingshu Li, and Raheem Beyah. Dsf-a distributed security framework for heterogeneous wireless sensor networks. In 2010-MILCOM 2010 Military Communications Conference, pages 1836–1843. IEEE, 2010.
- [14] Marco Valero, Sang Shin Jung, A Selcuk Uluagac, Yingshu Li, and Raheem Beyah. Di-sec: A distributed security framework for heterogeneous wireless sensor networks. IEEE, 2012.

- [15] Ismail Butun, Salvatore D Morgera, and Ravi Sankar. A survey of intrusion detection systems in wireless sensor networks. IEEE communications surveys & tutorials, 16(1):266–282, 2013.
- [16] Andriy Stetsko, Lukas Folkman, and Vashek Matyáš. Neighbor-based intrusion detection for wireless sensor networks. In 2010 6th International Conference on Wireless and Mobile Communications, pages 420–425. IEEE, 2010.
- [17] Fang Liu, Xiuzhen Cheng, and Dechang Chen. Insider attacker detection in wireless sensor networks. In IEEE INFOCOM 2007-26th IEEE International Conference on Computer Communications, pages 1937–1945. IEEE, 2007.
- [18] Michael Riecker. Lightweight Intrusion Detection in Wireless Sensor Networks. PhD thesis, Technische Universität Darmstadt, 2015.
- [19] Renu Laskar and Jeremy Lyle. Fall colouring of bipartite graphs and cartesian products of graphs. Discrete applied mathematics, 157(2):330– 338, 2009.
- [20] Michael R Garey and David S Johnson. Computers and intractability, volume 174. Freeman San Francisco, 1979.
- [21] Patrik Floréen, Petteri Kaski, and Jukka Suomela. A distributed approximation scheme for sleep sceduling in sensor networks. In 2007 4th Annual IEEE Communications Society Conference on Sensor, Mesh and Ad Hoc Communications and Networks, pages 152–161. IEEE, 2007.
- [22] Kamrul Islam, Selim G Akl, and Henk Meijer. Maximizing the lifetime of wireless sensor networks through domatic partition. In 2009 IEEE 34th Conference on Local Computer Networks, pages 436–442. IEEE, 2009.
- [23] Rajiv Misra and Chittaranjan Mandal. Efficient clusterhead rotation via domatic partition in self-organizing sensor networks. Wireless Communications and Mobile Computing, 9(8):1040–1058, 2009.
- [24] Brendan Mumey, Kelly Spendlove, and Binhai Zhu. Extending the lifetime of a wsn by partial covers. In 2013 IEEE International Conference on Communications (ICC), pages 1779–1783. IEEE, 2013.
- [25] Sriram V Pemmaraju and Imran A Pirwani. Energy conservation via domatic partitions. In Proceedings of the 7th ACM international symposium on mobile ad hoc networking and computing, pages 143–154, 2006.
- [26] Jiguo Yu, Qingbo Zhang, Dongxiao Yu, Congcong Chen, and Guanghui Wang. Domatic partition in homogeneous wireless sensor networks. Journal of Network and Computer Applications, 37:186–193, 2014.
- [27] Douglas Rall. A fractional version of domatic number. Congressus Numerantium, 74:100–106, 1990.
- [28] Uriel Feige, Magnús M Halldórsson, Guy Kortsarz, and Aravind Srinivasan. Approximating the domatic number. SIAM Journal on computing, 32(1):172–195, 2002.
- [29] Andrzej Czygrinow, M Hanćkowiak, E Szymańska, Wojciech Wawrzyniak, and Marcin Witkowski. Improved distributed local approximation algorithm for minimum 2-dominating set in planar graphs. Theoretical Computer Science, 662:1–8, 2017.
- [30] Hongyu Liang. The algorithmic complexity of k-domatic partition of graphs. In IFIP International Conference on Theoretical Computer Science, pages 240–249. Springer, 2012.
- [31] A Srinavasa Rao and C Pandu Rangan. Linear algorithm for domatic number problem on interval graphs. Information Processing Letters, 33(1):29–33, 1989.
- [32] Dhia Mahjoub, Angelika Leskovskaya, and David W Matula. Approximating the independent domatic partition problem in random geometric graphs-an experimental study. In CCCG, pages 195–198, 2010.
- [33] Saurav Pandit, Sriram V Pemmaraju, and Kasturi Varadarajan. Approximation algorithms for domatic partitions of unit disk graphs. In Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques, pages 312–325. Springer, 2009.
- [34] Jiguo Yu, Nannan Wang, Guanghui Wang, and Dongxiao Yu. Connected dominating sets in wireless ad hoc and sensor networks–a comprehensive survey. Computer Communications, 36(2):121–134, 2013.
- [35] Paul Erdos, Alfréd Rényi, et al. On the evolution of random graphs. Publ. Math. Inst. Hung. Acad. Sci, 5(1):17–60, 1960.
- [36] Albert-László Barabási and Réka Albert. Emergence of scaling in random networks. Science, 286(5439):509–512, 1999.
- [37] Hichem Kenniche and Vlady Ravelomananana. Random geometric graphs as model of wireless sensor networks. In 2010 The 2nd international conference on computer and automation engineering (ICCAE), volume 4, pages 103–107. IEEE, 2010.
- [38] Edward N Gilbert. Random plane networks. Journal of the society for industrial and applied mathematics, 9(4):533–543, 1961.
- [39] Milenko Jorgic, Michaël Hauspie, David Simplot-Ryl, and Ivan Stojmenovic. Localized algorithms for detection of critical nodes and links for

connectivity in ad hoc networks. In Mediterranean Ad Hoc Networking Workshop, page 12, 2004.

- [40] Furuzan Atay Onat, Ivan Stojmenovic, and Halim Yanikomeroglu. Generating random graphs for the simulation of wireless ad hoc, actuator, sensor, and internet networks. Pervasive and Mobile Computing, 4(5):597–615, 2008.
- [41] Vinod Kumar Verma, Surinder Singh, and Nagendra Prasad Pathak. Towards comparative evaluation of trust and reputation models over static, dynamic and oscillating wireless sensor networks. Wireless Networks, 23:335–343, 2017.
- [42] Adnan Ahmed, Kamalrulnizam Abu Bakar, Muhammad Ibrahim Channa, Khalid Haseeb, and Abdul Waheed Khan. A survey on trust based detection and isolation of malicious nodes in ad-hoc and sensor networks. Frontiers of Computer Science, 9:280–296, 2015.
- [43] Mario Strasser and Harald Vogt. Autonomous and distributed node recovery in wireless sensor networks. In Proceedings of the fourth ACM workshop on Security of ad hoc and sensor networks, pages 113–122, 2006.
- [44] Ka-Shun Hung, Chun-Fai Law, King-Shan Lui, and Yu-Kwong Kwok. On attack-resilient wireless sensor networks with novel recovery strategies. In 2009 IEEE Wireless Communications and Networking Conference, pages 1–6. IEEE, 2009.
- [45] Haythem Hayouni, Mohamed Hamdi, and Tai-Hoon Kim. A survey on encryption schemes in wireless sensor networks. In 2014 7th International Conference on Advanced Software Engineering and Its Applications, pages 39–43. IEEE, 2014.
- [46] Salim El Khediri. Wireless sensor networks: a survey, categorization, main issues, and future orientations for clustering protocols. Computing, pages 1–63, 2022.
- [47] Mahesh Pawar and Jitendra Agarwal. A literature survey on security issues of wsn and different types of attacks in network. Indian J. Comput. Sci. Eng, 8(2):80–83, 2017.
- [48] Ranjit Kumar, Sachin Tripathi, and Rajeev Agrawal. An analysis and comparison of security protocols on wireless sensor networks (wsn). In Design Frameworks for Wireless Networks, pages 3–21. Springer, 2020.
- [49] Lucia Keleadile Ketshabetswe, Adamu Murtala Zungeru, Mmoloki Mangwala, Joseph M Chuma, and Boyce Sigweni. Communication protocols for wireless sensor networks: A survey and comparison. Heliyon, 5(5):e01591, 2019.
- [50] Gergely Kovásznai, Balázs Erdélyi, and Csaba Biró. Investigations of graph properties in terms of wireless sensor network optimization. In 2018 IEEE International Conference on Future IoT Technologies (Future IoT), pages 1–8. IEEE, 2018.
- [51] Can Basaran, Kyoung-Don Kang, and H Suzer Mehmet. Hop-by-hop congestion control and load balancing in wireless sensor networks. In IEEE Local Computer Network Conference, pages 448–455. IEEE, 2010.
- [52] Yong Ding, Chen Wang, and Li Xiao. An adaptive partitioning scheme for sleep scheduling and topology control in wireless sensor networks. IEEE Transactions on Parallel and Distributed Systems, 20(9):1352–1365, 2008.
- [53] Dibakar Saha and Nabanita Das. Distributed area coverage by connected set cover partitioning in wireless sensor networks. arXiv preprint arXiv:1401.8152, 2014.



BENJAMIN FÖRSTER was born in Frankfurt (Oder), Germany in 1991 and received his B.Sc. and M.Sc. in Computer Science at Brandenburg University of Technology Cottbus-Senftenberg (B-TU), in Cottbus, Brandenburg, Germany in 2017 and 2020 respectively.

He is currently a Ph.D. Student at IHP in Frankfurt (Oder), Germany. His major field of study is security in wireless embedded resource constraint systems. Prior he worked as research assistant at

IHP and B-TU and software developer at Astronergy Solarmodule GmbH. His research interests encompass a range of topics, including the security of wireless resource-constrained embedded systems and the application of biologically inspired computing principles.



PETER LANGENDÖRFER holds a diploma and a doctorate degree in computer science from B-TU in Cottbus, Brandenburg, Germany received in 1995 and 2001 respectively.

He is with the IHP in Frankfurt (Oder) since 2000. There, he is leading the wireless systems department. From 2012 till 2020 he was leading the chair for security in pervasive systems at the Technical University of Cottbus-Senftenberg. Since 2020 he owns the chair wireless systems

at the Technical University of Cottbus-Senftenberg. His portfolio includes over 150 peer-reviewed technical articles that he has published, as well as 17 filed patents, with 11 already granted. He is associate editor of IEEE Access, IEEE Internet of Things, Peer-to-Peer Networking and worked as guest editor for many renowned journals e.g. Wireless Communications and Mobile Computing (Wiley) and ACM Transactions on Internet Technology. His areas of high interest include security for resource constraint devices, low-power protocols, efficient implementations of AI, and resilience.

Prof. Dr. Langendörfer is member of the "Gesellschaft für Informatik".



THOMAS HINZE was born in Halle (Saale), Germany in 1971. He received the Diploma degree in computer science from the Dresden University of Technology, Germany in 1997 and the Ph.D. degree in engineering sciences from the same institution in 2002. In 2012, he became a senior university lecturer at the Friedrich Schiller University Jena, Germany, along with his professorial dissertation.

He is author of three text books, more than 90

publications and holds two patents. His research interests include principles of biological and biologically inspired information processing like molecular computing, membrane computing, distributed computing, evolutionary computing, and systems biology. He is an editorial board member of the Springer Journal of Membrane Computing.

PD Dr. Hinze joined the Association for Computing Machinery (ACM) and engages in the International Membrane Computing Society (IMCS) as well as in the Institute for Systems and Technologies of Information, Control and Communication (INSTICC). He was a recipient of five Best Paper Awards.